

WESTERN AGRO TECH EQUIPMENT

Manufacturing Address:- Plot No- 162 , HSIIDC, IGC

Saha, Ambala, Haryana

Ph No. 7015458509, 8708401834

Email ID- westernagroequipment@gmail.com

GST No. 06AADFW4570G1Z4

Web site :-www.waeagri.com

.ISO 9001:2015 .ISO 14001:2015 .CE CERTIFIED CO.

Seed Grain Pre Cleaning & Fine Cleaning/Grading Manufacturers

And Exporters of High Quality Agriculture Equipments.

Ref : WES/QTN/21-22/283

Date :-05-03-2022

To

M/s Mangal Das Agro Producer Company
Solapur, Maharashtra

Sub: Quotation of Seed Grain Cleaning Grading Unit, Capacity 2.5-3TPH.

Dear Sir,

In reference to your telephonic discussion, we are submitting here our best offer for the supply of **Seed Grain Cleaning Grading Unit**.

We are pleased to introduce ourselves as one of the leading suppliers of Seed and Rice Processing Machinery in the country. Most of the products introduced by us save valuable man power. While ensuring highest quality precision and reliability.

Our unit is well equipped with ultra modern fully automatic and computerized manufacturing facilities CNC Punching Machine, CNC Bending Machine, Shearing Machines. The unit also has a fully equipped Research & Design centre with latest design software's. The Research & Design Centre has a pleasant atmosphere to work with an intention of designing world's best machines here in Western Agrotech Equipment.

We are looking forward for your valuable order.
Your fast reply will be highly appreciated.

Thanking You

For Western Agrotech Equipment

Sumidhe

Authorised Signatory

AUTHORIZED SIGNATORY

WESTERN AGRO TECH EQUIPMENT

Manufacturing Address:- Plot No- 162 , HSIIDC, IGC

Saha, Ambala, Haryana

Ph No. 7015458509, 8708401834

Email ID- westernagroequipment@gmail.com

GST No. 06AADFW4570G1Z4

Web site :-www.waeagri.com

.ISO 9001:2015 .ISO 14001:2015 .CE CERTIFIED CO.

Seed Grain Pre Cleaning & Fine Cleaning/Grading Manufacturers

And Exporters of High Quality Agriculture Equipments.

Sr.No.	ITEM NAME	RATE	QTY	AMOUNT
1.	<p>V. B Elevator (To feed Grader cum cleaner) Capacity : 3-4 Tons/hr. Discharge Ht.: as per site</p> <p>Self Supporting, centrifugal discharge Vertical Bucket Elevators have following standard features.</p> <p>V-BOTTOM BOOT ASSEMBLY: It is self-cleaning type. The thickness of the boot is not less than 3 mm M.S. Sheet .The pulley is mounted on a heavy-duty shaft on self aligned ball bearings. Belt tightened is provided with the help of square M.S bar for easy sliding of take up unit. Two removable slide gates are provided for easy and fast cleaning and rendering service to the bottom pulley. Boot pulley is of wing/screw type to prevent damage to the seed in between belt and pulley.</p> <p>HEAD CASING: It is made up of not less than 2.0 mm thick M.S. sheet. Detachable split cover with rubber/foam inside is provided for accessibility to head pulley. Head pulley is crowned for improved traction and is mounted on a heavy duty shaft and self aligned ball bearings. Geared motor is directly mounted on shaft for easy and quick fitting with 100% output and maintenance free operation 100% power transmission and maintenance free operation to reduce power consumption to achieve higher efficiency.</p> <p>BELT AND BELT SPEED: 5" width Nylon-to-Nylon belt are used for fastening of buckets (cups). The belt speed is less than 1 m/sec.</p> <p>BUCKETS: 5" Buckets are of self cleaning type, either HDPE or die pressed from M.S. Sheet not less than 1.6 mm thick are used. These buckets are fastened with cup-bolt and washers with belt. Spacers are provided between buckets and belt to prevent damage to the seeds.</p> <p>DISCHARGE PIPE: Suitable dia discharge pipe made not less than 1.60 mm M.S. Sheet with both end flanged are used for discharging the grains/seeds.</p> <p>ELECTRIC DRIVE: 1.0 hp geared motor of Crompton, ABB, Kirloskar, etc. on 440 V, 3Phase, 50 cycles, A.C. Supply. Starter,</p>	65,000/-	01	65,000/-

WESTERN AGRO TECH EQUIPMENT

Manufacturing Address:- Plot No- 162 , HSIIDC, IGC

Saha,Ambala,Haryana

Ph No. 7015458509,8708401834

Email ID- westernagroequipment@gmail.com

GST No. 06AADFW4570G1Z4

Web site :-www.waeagri.com

.ISO 9001:2015 .ISO14001:2015 .CE CERTIFID CO.

Seed Grain Pre Cleaning & Fine Cleaning/Grading Manufacturers

And Exporters of High Quality Agriculture Equipments.

	MCB of L&T / Siemens will be provided.			
2.	<p>Seed Grader Cum Cleaner (Model-WAE-G63)</p> <p>Capacity: Grading : up to 2.5-3 TPH (Based on Wheat)</p> <p>Specification : -</p> <p>Used for efficient cleaning of all types of cereal grains, paddy, rice, malting barley, coffee seeds and pre-cleaning of all types of seeds such as wheat, paddy, maize, millets, sunflower, soybean, oil seeds and also for rice & pulse milling plants</p> <p style="text-align: center;">No. of Screens : Three</p> <ul style="list-style-type: none">• Screen Size : 100cmx200cm• Power : 5 hp• No of Aspiration : Two• Screen Cleaning device : Top Screen (Balls) Middle & Bottom screens (Nylon Brush) <p style="text-align: center;">Seed Grader Cum Cleaner (L*W*H)</p> <p>Overall Length : 2950mm (9feet.6") Overall width : 1830mm (6feet.1") Total Height : 2545mm (8feet.3")</p> <ul style="list-style-type: none">• Sheet Brand : MS(JSW, Tata Steel)• Body brand : 6" channels heavy duty• Side sheets : 10,14,gauge• Bearing make : NRB/NBC/NTN etc.• Motor make : Crompton, ABB, etc. <p>Complete with one set of screen, electric motor/s, starter Switch, pulley guard, 2 no. Air bend and 1 mt long air trunk, Foundation bolt, Tool Kit, without air trunk and dust collector. The pulleys are made of high grade cast iron. The belts are of Fanner/Pix/make.</p> <p>All the metallic parts are made on CNC Machines like-Punching and bending machines. All shafts shall be provided EN-8 grade material.</p>	2,95,000/-	01	2,95,000/-

WESTERN AGRO TECH EQUIPMENT

Manufacturing Address:- Plot No- 162 , HSIIDC, IGC

Saha, Ambala, Haryana

Ph No. 7015458509, 8708401834

Email ID- westernagroequipment@gmail.com

GST No. 06AADFW4570G1Z4

Web site :-www.waeagri.com

.ISO 9001:2015 .ISO 14001:2015 .CE CERTIFIED CO.

Seed Grain Pre Cleaning & Fine Cleaning/Grading Manufacturers

And Exporters of High Quality Agriculture Equipments.

3.	<p>V. B Elevator (To feed Seed Magnetic Destoner)</p> <p>Capacity : 3-4 Tons/hr. Discharge Ht.: as per site</p> <p>Self Supporting, centrifugal discharge Vertical Bucket Elevators have following standard features.</p> <p>DUMP HOPPER: It is made up of 2 mm thick mild steel (M.S) Sheet.</p> <p>V-BOTTOM BOOT ASSEMBLY: It is self-cleaning type. The thickness of the boot is not less than 3 mm M.S. Sheet. The pulley is mounted on a heavy-duty shaft on self aligned ball bearings. Belt tightened is provided with the help of square M.S bar for easy sliding of take up unit.</p> <p>Two removable slide gates are provided for easy and fast cleaning and rendering service to the bottom pulley. Boot pulley is of wing/screw type to prevent damage to the seed in between belt and pulley.</p> <p>MIDDLE SECTION LEGS: Each section of leg is made up of not less than 1.6 mm thick M.S. Sheet. It is provided with flanges at both ends. Belt inspection door is provided at suitable height the first section of the leg will be 2.5mtr. high</p> <p>HEAD CASING: It is made up of not less than 2.0 mm thick M.S. sheet. Detachable split cover with rubber/foam inside is provided for accessibility to head pulley. Head pulley is crowned for improved traction and is mounted on a heavy duty shaft and self aligned ball bearings. Geared motor is directly mounted on shaft for easy and quick fitting with 100% output and maintenance free operation 100% power transmission and maintenance free operation to reduce power consumption to achieve higher efficiency.</p> <p>BELT AND BELT SPEED: 6" width Nylon-to-Nylon belt are used for fastening of buckets (cups). The belt speed is less than 1 m/sec.</p> <p>BUCKETS: 6" Buckets are of self cleaning type, either HDPE or die pressed from M.S. Sheet not less than 1.6 mm thick are used. These buckets are fastened with cup-bolt and washers with belt. Spacers are provided between buckets and belt to prevent</p>	65,000/-	01	65,000/-
----	---	----------	----	----------

WESTERN AGRO TECH EQUIPMENT

Manufacturing Address:- Plot No- 162 , HSIIDC, IGC

Saha, Ambala, Haryana

Ph No. 7015458509, 8708401834

Email ID- westernagroequipment@gmail.com

GST No. 06AADF4570G1Z4

Web site :-www.waeagri.com

.ISO 9001:2015 .ISO 14001:2015 .CE CERTIFIED CO.

Seed Grain Pre Cleaning & Fine Cleaning/Grading Manufacturers

And Exporters of High Quality Agriculture Equipments.

	<p>damage to the seeds.</p> <p>LADDER AND PLATFORM: ladder, service platform with suitable size and height shall be provided to enable accessibility to the head and shall be made of M.S</p> <p>ELECTRIC DRIVE: 1.0 hp geared motor of Crompton, ABB, Kirloskar, etc. on 440 V, 3Phase, 50 cycles, A.C. Supply. Starter, MCB of L&T / Siemens will be provided.</p>			
4.	<p>Magnetic Destoner (Model- WAE-D2)</p> <p>Specification :</p> <ul style="list-style-type: none"> • To separate stone & soil from the seed. • Capacity : 2.5-3 TPH. • Motor H.P. : 1 HP • Vibrator : 0.5 HP • Size : 100mm X1000mm • Magnet : N50High Graded • PU Belt : 1mm Thik • Power : 12000 Gauss Power <p style="text-align: center;">Magnetic Destoner</p> <ul style="list-style-type: none"> ○ Overall Length 1320mm(4.3feet) ○ Overall width 1636 mm(5.3feet) ○ Overall height 1505mm (4.9feet) <p>Complete with Feed hopper, Electric Control System, Starter Switch tool Kit etc.</p> <p>The pulleys are made of high grade cast iron. The belts are of Fanner/Pix/make.</p> <p>All the metallic parts are made on CNC Machines like-Punching and bending machines. All shafts shall be provided EN-8 grade material.</p>	3,15,000/-	01	3,15,000/-

WESTERN AGRO TECH EQUIPMENT

Manufacturing Address:- Plot No- 162 , HSIIDC, IGC

Saha, Ambala, Haryana

Ph No. 7015458509, 8708401834

Email ID- westernagroequipment@gmail.com

GST No. 06AADFW4570G1Z4

Web site :-www.waeagri.com

.ISO 9001:2015 .ISO 14001:2015 .CE CERTIFIED CO.

Seed Grain Pre Cleaning & Fine Cleaning/Grading Manufacturers

And Exporters of High Quality Agriculture Equipments.

5.	<p>V. B Elevator (To feed Gravity Separator)</p> <p>Capacity : 3-4 Tons/hr. Discharge Ht.: as per site</p> <p>Self Supporting, centrifugal discharge Vertical Bucket Elevators have following standard features.</p> <p>DUMP HOPPER: It is made up of 2 mm thick mild steel (M.S) Sheet.</p> <p>V-BOTTOM BOOT ASSEMBLY: It is self-cleaning type. The thickness of the boot is not less than 3 mm M.S. Sheet. The pulley is mounted on a heavy-duty shaft on self aligned ball bearings. Belt tightened is provided with the help of square M.S bar for easy sliding of take up unit.</p> <p>Two removable slide gates are provided for easy and fast cleaning and rendering service to the bottom pulley. Boot pulley is of wing/screw type to prevent damage to the seed in between belt and pulley.</p> <p>MIDDLE SECTION LEGS: Each section of leg is made up of not less than 1.6 mm thick M.S. Sheet. It is provided with flanges at both ends. Belt inspection door is provided at suitable height the first section of the leg will be 2.5mtr. high</p> <p>HEAD CASING: It is made up of not less than 2.0 mm thick M.S. sheet. Detachable split cover with rubber/foam inside is provided for accessibility to head pulley. Head pulley is crowned for improved traction and is mounted on a heavy duty shaft and self aligned ball bearings. Geared motor is directly mounted on shaft for easy and quick fitting with 100% output and maintenance free operation 100% power transmission and maintenance free operation to reduce power consumption to achieve higher efficiency.</p> <p>BELT AND BELT SPEED: 5" width Nylon-to-Nylon belt are used for fastening of buckets (cups). The belt speed is less than 1 m/sec.</p> <p>BUCKETS: 5" Buckets are of self cleaning type, either HDPE or die pressed from M.S. Sheet not less than 1.6 mm thick are used. These buckets are fastened with cup-bolt and washers with belt. Spacers are provided between buckets and belt to prevent</p>	65,000/-	01	65,000/-
----	--	----------	----	----------

WESTERN AGRO TECH EQUIPMENT

Manufacturing Address:- Plot No- 162 , HSIIDC, IGC

Saha, Ambala, Haryana

Ph No. 7015458509, 8708401834

Email ID- westernagroequipment@gmail.com

GST No. 06AADF4570G1Z4

Web site :-www.waeagri.com

.ISO 9001:2015 .ISO 14001:2015 .CE CERTIFIED CO.

Seed Grain Pre Cleaning & Fine Cleaning/Grading Manufacturers

And Exporters of High Quality Agriculture Equipments.

	<p>damage to the seeds.</p> <p>LADDER AND PLATFORM: ladder, service platform with suitable size and height shall be provided to enable accessibility to the head and shall be made of M.S</p> <p>ELECTRIC DRIVE: 1.0 hp geared motor of Crompton, ABB, Kirloskar, etc. on 440 V, 3Phase, 50 cycles, A.C. Supply. Starter, MCB of L&T / Siemens will be provided.</p>			
6.	<p>Gravity Separator (Model- WAE-GS13)</p> <p>Specification:</p> <ul style="list-style-type: none"> The Machine is suitable for removing impurities and achieving very high grading quality in any free flowing granular material, Grain Seed and Spices etc. No. of fan : 5 fan Capacity : 3-4 TPH (Based on Wheat) <p>Deck Size (L*W)</p> <ul style="list-style-type: none"> Overall Length : 2400 mm (7.8feet) Overall width : 1100 mm (3.6feet) Deck motor : 1hp <p>Gravity Separator Size (L*W*H)</p> <ul style="list-style-type: none"> Overall Length : 2750mm (9feet.2") Overall width : 1400mm (4feet.5") Total Height : 2515mm (8feet,2") with Hopper Blower motor : 7.5 hp No. of windows : 8 <ul style="list-style-type: none"> Sheet Brand : MS(JSW, Tata Steel) Body brand : 6" channels heavy duty Side sheets : 10,14 gauge Deck top sieves : S.S. made Bearing make : NRB/NBC/NTN etc. Motor make : Crompton, ABB, etc. 	2,70,000/-	01	2,70,000/-

WESTERN AGRO TECH EQUIPMENT

Manufacturing Address:- Plot No- 162 , HSIIDC, IGC

Saha,Ambala,Haryana

Ph No. 7015458509,8708401834

Email ID- westernagroequipment@gmail.com

GST No. 06AADFW4570G1Z4

Web site :-www.waeagri.com

.ISO 9001:2015 .ISO14001:2015 .CE CERTIFID CO.

Seed Grain Pre Cleaning & Fine Cleaning/Grading Manufacturers

And Exporters of High Quality Agriculture Equipments.

	<p>Variable Frequency Drive to control Deck Speed precisely Electronically.</p> <p>Complete with 250kg feed hopper,1no.deck for any crops, Air Filters ,spouts, Electric motors of make-like Kirloskar, Crompton, Siemens etc.</p> <p>The pulleys are made of high grade cast iron. The belts are of Fanner/Pix/make.</p> <p>All the metallic parts are made on CNC Machines like-Punching and bending machines. All shafts shall be provided EN-8 grade material.</p>			
7.	<p>V. B Elevator(To feed Final Seed)</p> <p>Capacity : 3-4 Tons/hr. Discharge Ht.: as per site</p> <p>Self Supporting, centrifugal discharge Vertical Bucket Elevators have following standard features.</p> <p>DUMP HOPPER: It is made up of 2 mm thick mild steel (M.S) Sheet.</p> <p>V-BOTTOM BOOT ASSEMBLY: It is self-cleaning type. The thickness of the boot is not less than 3 mm M.S. Sheet .The pulley is mounted on a heavy-duty shaft on self aligned ball bearings. Belt tightened is provided with the help of square M.S bar for easy sliding of take up unit.</p> <p>Two removable slide gates are provided for easy and fast cleaning and rendering service to the bottom pulley. Boot pulley is of wing/screw type to prevent damage to the seed in between belt and pulley.</p> <p>MIDDLE SECTION LEGS: Each section of leg is made up of not less than 1.6 mm thick M.S. Sheet. It is provided with flanges at both ends. Belt inspection door is provided at suitable height the first section of the leg will be 2.5mtr. high</p> <p>HEAD CASING: It is made up of not less than 2.0 mm thick M.S. sheet. Detachable split cover with rubber/foam inside is provided for accessibility to head pulley. Head pulley is crowned</p>	65,000/-	01	65,000/-

WESTERN AGRO TECH EQUIPMENT

Manufacturing Address:- Plot No- 162 , HSIIDC, IGC

Saha, Ambala, Haryana

Ph No. 7015458509, 8708401834

Email ID- westernagroequipment@gmail.com

GST No. 06AADFW4570G1Z4

Web site :-www.waeagri.com

.ISO 9001:2015 .ISO 14001:2015 .CE CERTIFIED CO.

Seed Grain Pre Cleaning & Fine Cleaning/Grading Manufacturers

And Exporters of High Quality Agriculture Equipments.

	<p>for improved traction and is mounted on a heavy duty shaft and self aligned ball bearings. Geared motor is directly mounted on shaft for easy and quick fitting with 100% output and maintenance free operation 100% power transmission and maintenance free operation to reduce power consumption to achieve higher efficiency.</p> <p>BELT AND BELT SPEED: 5" width Nylon-to-Nylon belt are used for fastening of buckets (cups). The belt speed is less than 1 m/sec.</p> <p>BUCKETS: 5" Buckets are of self cleaning type, either HDPE or die pressed from M.S. Sheet not less than 1.6 mm thick are used. These buckets are fastened with cup-bolt and washers with belt. Spacers are provided between buckets and belt to prevent damage to the seeds.</p> <p>LADDER AND PLATFORM: ladder, service platform with suitable size and height shall be provided to enable accessibility to the head and shall be made of M.S</p> <p>ELECTRIC DRIVE: 1.0 hp geared motor of Crompton, ABB, Kirloskar, etc. on 440 V, 3Phase, 50 cycles, A.C. Supply. Starter, MCB of L&T / Siemens will be provided.</p>			
	Total Amount			11,40,000 /-

AREA REQUIRED	L X W X H 35 X 20 X 18
POWER REQUIRED IN HP	19HP
POWER REQUIRED IN KW	14KW

WESTERN AGRO TECH EQUIPMENT

Manufacturing Address:- Plot No- 162 , HSIIDC, IGC

Saha, Ambala, Haryana

Ph No. 7015458509, 8708401834

Email ID- westernagroequipment@gmail.com

GST No. 06AADF4570G1Z4

Web site :-www.waeagri.com

.ISO 9001:2015 .ISO 14001:2015 .CE CERTIFIED CO.

Seed Grain Pre Cleaning & Fine Cleaning/Grading Manufacturers

And Exporters of High Quality Agriculture Equipments.

TERMS & CONDITIONS

1. **Price** :Our prices are Ex-work Ambala.
2. **IGST** : Extra.
3. **Transportation**: It will be to Buyer Account, our site loading to be our account but Unloading to be buyer account.
Payment: 50% Advance along with order & balance 50% before Dispatch against performance invoice.
4. **Delivery**: Within 25-30 days from the date of receipt of technically & commercially cleared order.
5. **Validity**: 30 days from the date of Quotation/Offer.
6. **Guarantee**: We undertake the responsibility to rectify any defect in equipment supplied by us due to bad workmanship or defective material, provided the defects are brought to our notice within 12 (twelve) calendar months from the date of supply. For any defect brought to our notice after the guarantee period we will not be held responsible and if we are called upon to rectify those defects, extra charges will be payable to us. But we will be not taking any responsibility for any defect in electric items. Due to spites Voltage Fluctuation
7. **Performance**: Our plant is guaranteed to meet the related performance as per our offer for a period of one year from the date of supply. We shall attend to any faults within the guarantee period in case it is brought to our notice immediately and rectify the problem.
8. **Installation and commissioning**: - It includes the installation and supervision of all the machines supplied by us in India. It do not include civil work material like cement, sand, concrete, mason and civil work labor etc., For installation and commissioning, the equipments and tools required shall be provided by us. Like tools & tackles, supporting mcs like Crain, chain block etc., all electrical like cable, earth wire, cable tray, and fitting shall be in the scope of customer/buyer. The arrangement for security, water facility, electric supply etc. shall be borne/made by customer
9. **Force Majeure**: Our offer is subject to force Majeure clause. We shall not be held responsible for any delay in execution of the work for the causes beyond our control such as war, revolution, strike, epidemic accidental fire, flood or any other act of God.
10. **Jurisdiction**: Any legal dispute arising of the resultant contract will be subject to the jurisdiction of Ambala court, in case same is not settled mutually.

Thanking You

AUTHORIZED SIGNATORY