



An ISO 9001:2008 Company


AIWA Junction Box with Lighting Protection Components

AIWA Load Cell Junction box is designed for the use of summing the signal outputs from multiple load cells. The junction box is constructed using thick MS sheet and is powder coated to withstand harsh environmental conditions. Protective rubber seal for the lid, airtight cable glands for routing cables ensure prevention of moisture & dust ingress, thus preventing

Signal distortion. A high quality signal thus obtained, offers higher resolution in the constructed weighing scale.

| | |
|--------------------------|--|
| Load cell connectivity | 8(AJB08) |
| Corner adjustment | Not required in Digital Load cell system |
| Section load trimming | Not required in Digital Load Cell System |
| Electrical protection | Special lightning protection components for protection against transients induced by line voltage spikes, surges and lightning |
| Environmental protection | Rubber Seal Gasket on top cover and air tight cable glands for entry of load cell cables and indicator cables |
| Dimensions (mm) | AJB08:280x190X55 |
| Weight | 2.0 - 3.5 Kg |



Commercial Offer for Weigh Bridge

An ISO 9001:2008 Company

| Model | Capacity | Accuracy | No. of Load Cell | Platform Size | Price Rs. / Unit |
|--------|----------|----------|------------------|---------------|------------------|
| AWB10T | 10MT | 1 Kg | 4 (Digital) | 16x8ft | Rs. 3,65,000/- |

Additional Scope Of Supply

| | |
|------------------------------|-----------|
| Printer (Dot Matrix) | Extra |
| Software For MIS Reports | Inclusive |
| Supervision For Installation | Extra |
| Govt. Stamping Expenses | Extra |
| Transportation | Extra |
| G.S.T.18% | Extra |

Note : Customer have to arrange NOC from concerned authorities such as Collector/ Municipality/ Corporation/Gram Panchayat etc... At the time of weigh bridge stamping.

