



# Skylark Engineering Technologies

Manufacturers of all type Laboratory Equipment's  
An ISO 9001-2015 Certified Company

## QUOTATION

Date: 22.07.2022

QTN no:1525

**TO,**

**Shree Agro Krushi Farmers Producer co Ltd**

Mumbai, Maharashtra, India

Mo: 9029684584

Mail id: info@shreeagrofpc.com

Kind attn.: Mr Avinash Kumar

### **SUB: Your requirement for Air Shower.**

Dear Sir,

We refer to our discussions regarding the Air Shower and as requested by you, we have enclosed herewith our offer for **Air Shower** for your ready reference.


We are confident of meeting the productivity and the Air cleanliness level and the quality which is among the best in the industry. We also assure you of our best services at all the times and the co-ordination in setting of System for achieving Air cleanliness standard. We request you to kindly go through the same and in case of any doubts, please feel free to contact us anytime.

We look forward to your valuable order. Thanking you, while assuring you of our best attention at all the times.

Yours Truly,

**Mrs. Rina Deshmukh**

**Contact No.:8956167259**





# Skylark Engineering Technologies

Manufacturers of all type Laboratory Equipment's  
An ISO 9001-2015 Certified Company

## AIR SHOWER

'Skylark' set a benchmark in the industry for manufacturing and supplying Air Shower. These clean room entry systems decontaminate workers and products entering a clean room environment. Clean Air Products offers a range of air shower configurations that work efficiently to reduce particle loads. Our staff of experts will ensure you get the air shower that fits your needs exactly. The offered air Shower is made from high quality materials in our sophisticated production unit. It is used for preventing infiltration of microbes, dust and insects in sterilized cabinets. This shower finds wide application in the health care centers, pharmaceutical industry and food processing units.

### Standard Features

- Durable and Clean Room-Approved Painted Cold Rolled Steel Shell.
- No Silicone used - only Low-Out gassing Epoxy or Urethane Sealant.
- (2) Anodized Aluminum framed Safety Glass Doors with Hydraulic Door Closers.
- Surface-mounted LED Light Fixture with Wall Switch.
- **(16) Adjustable Nozzles in SS 304.**
- Removable High-Pressure Interior Nozzle on Wall Panels.
- NOZZLE WITH 25 MM BORE.
- 4900 FPM (25 m/s) Average Nozzle Velocity.
- Programmable Microprocessor PLC with 0-30 second adjustable run time and 0-10 second adjustable wait time.


### PERFORMANCE:

Air Cleanness: - Class 100 (As per U.S. Fed. Std. 209E)

**CLASS ISO 5 (AS PER ISO 9001:2015)**

Air Jet Velocity: -Side Nozzles 25 M/Sec +/- 1 M/sec.

Noise Level. -Less than 80 Db when ambient sound level is not greater than 60 Db.






# Skylark Engineering Technologies

Manufacturers of all type Laboratory Equipment's

An ISO 9001-2015 Certified Company

<b>Model No</b>	<b>SET- AS SINGLE PERSON SINGLE DOOR ENTRY &amp; EXIT</b>
MOC	<b>MS POWDER COATED</b>
Overall Size (mm)	1500(L) X 1000(D) X 2200(H)mm
Working Area Size (mm)	900(L) X 920(D) X 2020(H)mm
Main Filters	Mini-pleat box type 0.3 microns HEPA filter, efficiency 99.97 % down to 0.3micron Particle size, Aluminum Anodized Casing. <b>Size: 610X610X70mm QTY-2 No. s</b>
Pre-Filters	Box type pleated efficiency 98 % down to 5 microns, HDPE + Non Woven + HDPE mesh media, aluminum casing. <b>Size: 595 mm x 295mm x 50 mm Qty-2 Nos</b>
Digital Display Control Unit	Entry & Exit Button (Emergency Stop Button with Programmable Unit)
Blower	Model: DI150-2E-S8 Supply-230VAC, Single Phase,50 Hz, Rpm-2300, AIR FLOW-1200 CMH <b>CFM- 706 per blower, Total cfm-1412, WATT-470, QTY - 2 NOS</b>
Blower Timer	Max. 2 Minutes. Adjustable.
Body	<b>Complete body MS powder coated 1.2 mm thk &amp; bottom with SS304 1.5 mm thk.</b>
Doors	40 mm thick, sandwiched type, MS material completes in all respect including hinges, handles door closers & view panels with swing outside.
Interlocking & Controls	Micro controller-based controller
Air Nozzles	Embossed air out-let nozzles on Right - left side, Top side <b>Left Side - 7 Nos., Right Side - 7 No's, Top Side-2 No's</b>
Arrangement of Lighting	Concealed type Led Fitting, 12 Watt - 2 NOS
Power Supply Cable	1.5 mm Sq. 4 core x 3 Mtrs. Flexible
Supply Provision	230 VAC, With Earthling





# Skylark Engineering Technologies

Manufacturers of all type Laboratory Equipment's

An ISO 9001-2015 Certified Company

<b>Price</b>	<b>Rs. 1,79,484/- Each Air Shower (Complete MS POWDER COATED)</b>
--------------	---

TERMS & CONDITIONS VALIDITY: 30 DAYS	
PRICE	Above prices is Ex-factory, PUNE
GST	GST 18 % EXTRA.
DELIVERY PERIOD	3-4 week Order Confirmation. Techno /Commerce Clear Order.
INSPECTION	Inspection & Demonstration at Our Works.
PAYMENT	50 % Advance & 50% Before dispatch.
INSTALLATION CHARGES	7 % on basic Value.
PACKING	Bubble packing
FREIGHT	Your Account.
INSURANCE	Any Breakage or Loss in Transit Is to Be Covered by Insure and It Is Extra. In the Event of Claim Formalities to Be Done by You.
SERVICE	Within 24 hours apart of India.
WARRANTY	12 Months Against Manufacturing Defects Except Glass Plastic & Rubber Parts or Part Thereof & Fuses Batteries from The Date of Dispatch.
Note: loading, unloading & shifting of material not in our scope. Scaffolding, ladder etc. not in our scope. Civil works not in our scope.	

Special Condition: PO should be in favor of: -

**SKYLARK ENGINEERING TECHNOLOGIES | SR. No -72/02 Jadhav Industrial Estate, Dhayari, Pune-4110041 Website- [www.skylarkgroups.co.in](http://www.skylarkgroups.co.in) Email -[sales.pune@skylarkgroup.co.in](mailto:sales.pune@skylarkgroup.co.in)**





# Skylark Engineering Technologies

Manufacturers of all type Laboratory Equipment's

An ISO 9001-2015 Certified Company

---

