



TULSI AGRO ENGI MECH PVT. LTD.

QUOTATION

ORIGINAL

M/S. YASHWINI KRUSHI MITRA FARMER PRODUCER CO. LTD., AT.PO. NITALI, TQ. DIST. : DHARASHIV KIND ATTEN. : MR. MAHAVEER NIKTE SIR 9922703243		Quotation No:Q 402/7T			
SEED GRAIN PROCESSING PLANT CAPACITY_4TPH		Date:26/05/2023			
No.	Particulars	HP	QTY.	Rate	Amount
1	DUMP HOPPER		1	35,000	35,000.00
2	VERTICAL BUCKET ELEVATOR Overall height: Feet Power: 2HP with Gear motor All sheet metal components shall be manufactured on CNC Machine. Head casing, boot casing and leg casing made of 2/3/1.6 mm or more GI sheet respectively. Spouting, spout sections, discharge valve, ladder, service platform, boot plate, take up unit, hopper with grating and feed control gate shall be of MS. Belt should be 8 mm Cotton Belt Buckets shall be PU/NYLON/HDPE, Self-cleaning type. Spacers shall be providing in between belt and buckets to prevent damage to seeds. Boot pulley shall be wing type to prevent lodging of seeds between pulley and belt. Head pulley shall be rubberiest and crowned for improved traction. Sprocket shall be TLB type for easy and quick fitting. Belt speed should not be exceed 1m/sec. Height of delivery as per requirement (as per height of pre cleaner o floor to be accommodated within existing building roof height.)These can also be integrated with horizontal or inclined trough belt conveyor system for fast and efficient movement & handling of raw material Of raw material	2 HP	1	99,000	99,000.00

Office: 1302, Twin star North Tower, 150 ft. ring road, Nr. Nana Mava circle, Rajkot-360005

Unit 1:- 14, Ankur Com. Complex, Nr. Gujarat Alloy Cast, Shapar (Veraval) Dist- Rajkot-360024

Unit 2 & 3 : RSN 50/2,Plot No. 1 & RSN 44/1, Plot No. 1, Bharudi Village Main Road, B/h Ajayraj Hotel, N.H.27, AT : Bharudidist : Rajkot, Gujarat(India).




Contact Us: - Mo-+91 94283 46905, Mo- +91 98796 13955

Email: - salestulsiagro@gmail.com, chiragbhalodiya@gmail.com

Website: - www.tulsiagrofood.com



TULSI AGRO ENGI MECH PVT. LTD.

					
3	<p>FINE-CLEANER WITH CLASSIFIER With stand -3 screen grader with suction fan of 7.5 HP & Vibrator sieve –boat on 2 HP.&vibro feeder on 80w single phase. Capacity 4 ton per hour Power :7.5+2=9.5 HP SIZE:63”X111” Screen SIZE:</p> <ul style="list-style-type: none"> • 43”x91” -2 nos zali • 43”x34” -1 nos zali <p>M.O.C.- Mild Steel G.I. Screen This is very common and simple process to clean any grains and pulses. It generally used rubber balls and nett for cleaning removing the husk and bigger as well as smaller size and low weight material from grains. It is aslo attached with blower.Final Material gets totally clean and pure.</p> <div style="display: flex;">   </div>	7.5+2=9.5 HP	1	5,50,000	5,50,000.00
4	<p>DUST CYCLONE</p>		1	55,000	55,000.00

Office: 1302, Twin star North Tower, 150 ft. ring road, Nr. Nana Mava circle, Rajkot-360005

Unit 1:- 14, Ankur Com. Complex, Nr. Gujarat Alloy Cast, Shapar (Veraval) Dist- Rajkot-360024

Unit 2 & 3 : RSN 50/2,Plot No. 1 & RSN 44/1, Plot No. 1, Bharudi Village Main Road, B/h Ajayraj Hotel, N.H.27, AT : Bharudidist : Rajkot, Gujarat(India).


Contact Us: - Mo-+91 94283 46905, Mo- +91 98796 13955

Email: - salestulsiagro@gmail.com, chiragbhalodiya@gmail.com

Website: - www.tulsiagrofood.com



TULSI AGRO ENGI MECH PVT. LTD.

5	<p>VERTICAL BUCKET ELEVATOR Power: 2 HP with Gear motor All sheet metal components shall be manufactured on CNC Machine. Head casing, boot casing and leg casing made of 2/3/1.6 mm or more GI sheet respectively. Spouting, spout sections, discharge valve, ladder, service Platform, boot plate, take up unit, hopper with grating and feed control gate shall be of MS. Belt should be 8 mm Cotton Belt Buckets shall be PU/NYLON/HDPE, Self-cleaning type. Spacers shall be providing in between belt and buckets to prevent damage to seeds. Boot pulley shall be wing type to prevent lodging of seeds between pulley and belt. Head pulley shall be rubberiest and crowned for improved traction. Sprocket shall be TLB type for easy and quick fitting. Belt speed should not be exceed 1m/sec. Height of delivery as per requirement (as per height of pre cleaner o floor to be accommodated within existing building roof height.)These can also be integrated with horizontal or inclined trough belt conveyor system for fast and efficient movement & handling of raw material</p> 	2 HP	1	99,000	99,000.00
6	<p>GRAVITY SEPARATOR SIZE :- L- 144"x W-42"x H-72" Power : 10HP+2HP=12 HP with S.S. 304 Deck with auto greasing system for all bearings On the basis of differences in specific gravity, the Gravity Separator are mainly used to classify and eliminate stones grain.In this thereare 7 fan used in that gravity. It will separate</p>	10+2= 12 HP	1	6,00,000	6,00,000.00

Office: 1302, Twin star North Tower, 150 ft. ring road, Nr. Nana Mava circle, Rajkot-360005

Unit 1:- 14, Ankur Com. Complex, Nr. Gujarat Alloy Cast, Shapar (Veraval) Dist- Rajkot-360024

Unit 2 & 3 : RSN 50/2,Plot No. 1 & RSN 44/1, Plot No. 1, Bharudi Village Main Road, B/h Ajayraj Hotel, N.H.27, AT : Bharudidist : Rajkot, Gujarat(India).


Contact Us: - Mo-+91 94283 46905, Mo- +91 98796 13955

Email: - salestulsiagro@gmail.com, chiragbhalodiya@gmail.com

Website: - www.tulsiagrofood.com



TULSI AGRO ENGI MECH PVT. LTD.

	<p>the grains by the quality and weight.</p> 				
7	<p>VERTICAL BUCKET ELEVATOR Power: 2HP with Gear motor All sheet metal components shall be manufactured on CNC Machine. Head casing, boot casing and leg casing made of 2/3/1.6 mm or more GI sheet respectively. Spouting, spout sections, discharge valve, ladder, service platform, boot plate, take up unit, hopper with grating and feed control gate shall be of MS. Belt should be 8 mm Cotton Belt Buckets shall be PU/NYLON/HDPE, Self-cleaning type. Spacers shall be providing in between belt and buckets to prevent damage to seeds. Boot pulley shall be wing type to prevent lodging of seeds between pulley and belt. Head pulley shall be rubberiest and crowned for improved traction. Sprocket shall be TLB type for easy and quick fitting. Belt speed should not be exceed 1m/sec. Height of delivery as per requirement (as per height of pre cleaner o floor to be accommodated within existing building roof height.) These can also be integrated with horizontal or inclined trough belt conveyor system for fast and efficient movement & handling of raw material</p> 	4 HP	2	1,10,000	2,20,000.00

Office: 1302, Twin star North Tower, 150 ft. ring road, Nr. Nana Mava circle, Rajkot-360005

Unit 1:- 14, Ankur Com. Complex, Nr. Gujarat Alloy Cast, Shapar (Veraval) Dist- Rajkot-360024

Unit 2 & 3 : RSN 50/2, Plot No. 1 & RSN 44/1, Plot No. 1, Bharudi Village Main Road, B/h Ajayraj Hotel, N.H.27, AT : Bharudidist : Rajkot, Gujarat(India).


Contact Us: - Mo-+91 94283 46905, Mo- +91 98796 13955

Email: - salestulsiagro@gmail.com, chiragbhalodiya@gmail.com

Website: - www.tulsiagrofood.com



TULSI AGRO ENGI MECH PVT. LTD.

8	<p>VERTICAL BUCKET ELEVATOR Power: 2HP with Gear motor All sheet metal components shall be manufactured on CNC Machine. Head casing, boot casing and leg casing made of 2/3/1.6 mm or more GI sheet respectively. Spouting, spout sections, discharge valve, ladder, service platform, boot plate, take up unit, hopper with grating and feed control gate shall be of MS. Belt should be 8 mm Cotton Belt Buckets shall be PU/NYLON/HDPE, Self-cleaning type. Spacers shall be providing in between belt and buckets to prevent damage to seeds. Boot pulley shall be wing type to prevent lodging of seeds between pulley and belt. Head pulley shall be rubberiest and crowned for improved traction. Sprocket shall be TLB type for easy and quick fitting. Belt speed should not be exceed 1m/sec. Height of delivery as per requirement (as per height of pre cleaner o floor to be accommodated within existing building roof height.)These can also be integrated with horizontal or inclined trough belt conveyor system for fast and efficient movement & handling of raw material</p> 	2 HP	1	99,000	99,000.00
9	<p>MAGNETIC DESTONER ROLL SIZE:-1250MM Magnetic De-stoner Machine is designed mainly for removing any sort of impurities from wheat, rice, grain and other such materials. It can kick out mud balls, black stones and other paramagnetic impurities, which ease color sorter process easier Besides, giving protection to the food items; it protects the machines like polishers or sizes from any unnecessary damages. Moreover, Magnetic Grain De-stoner can boost efficiency and overall productivity. Industrial Magnetic</p>	2 HP	1	3,50,000	3,50,000.00

Office: 1302, Twin star North Tower, 150 ft. ring road, Nr. Nana Mava circle, Rajkot-360005

Unit 1:- 14, Ankur Com. Complex, Nr. Gujarat Alloy Cast, Shapar (Veraval) Dist- Rajkot-360024

Unit 2 & 3 : RSN 50/2,Plot No. 1 & RSN 44/1, Plot No. 1, Bharudi Village Main Road, B/h Ajayraj Hotel, N.H.27, AT : Bharudidist : Rajkot, Gujarat(India).


Contact Us: - Mo-+91 94283 46905, Mo- +91 98796 13955

Email: - salestulsiagro@gmail.com, chiragbhalodiya@gmail.com

Website: - www.tulsiagrofood.com



TULSI AGRO ENGI MECH PVT. LTD.

	De-stoner ensures the safety or cleaning of the food. Its performance is incomparable and worth Applauding.				
					
10	PACKING BIN WITH SUPPORTING STRUCTURE			1,20,000	1,20,000.00
14	Extra Scree Set		4	42,000	1,68,000.00
14	PANEL BOARD			1,55,000	1,55,000.00
15	INSTALLATION & COMMISSING			1,50,000	1,50,000.00
				Sub.Total	26,90,000.00
				18% GST	4,84,200.00
				TOTAL	31,74,200.00

AMOUNT IN WORD- Rs. THIRTY ONE LAC SEVENTY FOUR THOUSAND TWO HUNDRED RUPEE ONLY.

Terms & condition:

- All price are ex our workshop
- GST 18% Extra as per government rules
- Capacity 4 Ton per hour (Input basis of wheat)
- All plant erection accessories are included.
- Civil work at party scope
- With electric motor & panel board
- Unloading at party scope
- Electrical wires party scope
- Advance payment is not refundable if order will be cancel.
- Welding machine & local 2 to 3 labor required at party scope for installation time.
- Quotation valid for 60 days from the date of quotation.
- Our technician's food & accommodation provided by party scope
- Structure Fabrication will be Included

Office: 1302, Twin star North Tower, 150 ft. ring road, Nr. Nana Mava circle, Rajkot-360005

Unit 1:- 14, Ankur Com. Complex, Nr. Gujarat Alloy Cast, Shapar (Veraval) Dist- Rajkot-360024

Unit 2 & 3 : RSN 50/2, Plot No. 1 & RSN 44/1, Plot No. 1, Bharudi Village Main Road, B/h Ajayraj Hotel, N.H.27, AT : Bharudidist : Rajkot, Gujarat(India).

Contact Us: - Mo-+91 94283 46905, Mo- +91 98796 13955

Email: - salestulsiagro@gmail.com, chiragbhalodiya@gmail.com

Website: - www.tulsiagrofood.com



TULSI AGRO ENGI MECH PVT. LTD.

Payment condition:

25% Payment at order time

75% Payment at before delivery

RS. TWENTY ONE LAKH NINETY ONE THOUSAND RUPESS ONLY

GST No-24AAFCT8162Q1ZO

FOR, TULSI AGRO ENGI MECH PVT.LTD.

OUR BANK- BANK OF INDIA

BHAKTI NAGAR BRANCH- RAJKOT

A/C NO.312130110000296

IFSC CODE:BKID0003121AUTHO. SIGNETURE

Office: 1302, Twin star North Tower, 150 ft. ring road, Nr. Nana Mava circle, Rajkot-360005

Unit 1:- 14, Ankur Com. Complex, Nr. Gujarat Alloy Cast, Shapar (Veraval) Dist- Rajkot-360024

Unit 2 & 3 : RSN 50/2,Plot No. 1 & RSN 44/1, Plot No. 1, Bharudi Village Main Road, B/h Ajayraj Hotel, N.H.27, AT : Bharudidist : Rajkot, Gujarat(India).

Contact Us: - Mo-+91 94283 46905, Mo- +91 98796 13955

Email: - salestulsiagro@gmail.com, chiragbhalodiya@gmail.com

Website: - www.tulsiagrofood.com