

Client:	M/s VISHAL SUDAM ADSUL			
Location:	TARADGAON TAL-PHALTAN DIST-SATARA			
ABSSTRACT				
It. No.	Description	Unit	Qty	Remark
1	Dressing, Leveling, Compaction, Preparation of base for Grade Slab.			
		SQMT	1060.75	SSR.Item no. 21.34
2	Providing & injecting chloropyriphos Emulsifiable 1% concentrations. by wt for pre-construction Anti-termite Treatment & creating a chemical barrier (through agency approved by Consultants), under & all around foundation pits, wall trenches, basement excavation, top surface of plinth filling ,junction of wall & floor, along the external perimeter of building, expansion joints, surrounding of pipes, water conduits or at places suggested by Engineer In Charge.			
		SQMT	952.75	SSR.Item no.21.22
3	Providing & Laying dry stone Rubble Soling with maximum 230mm size hard stone set in regular lines, hand packed and interstices thoroughly filled with small chips including filling in with good quality murum brought from outside and compacted with 8 to 10 ton rollers and spreading 12mm layer of grit on top etc complete as directed by Engineer In Charge.			
		CUM	243.97	SSR.Item no.21.38

4	Providing and laying plain cement concrete with 20 mm down graded coarse aggregate in blinding layer/fill under RCC. & masonry foundations, bottom of pits, sumps, channels, tie beams, grade slabs, floorings, footings, tanks, storm water drain, pipe encasing including ramming , leveling, curing etc complete as directed By Engineer In Charge.			
		CUM	8.10	SSR.Item no.24.1
5	Providing and placing reinforced concrete M25 for slab on grade or on floor with coarse aggregate of size 20mm downgraded excluding reinforcement but including side shuttering and construction in panels / strip method including providing necessary construction/ contraction/ expansion joints as shown on drawing and joints required at various locations like equipment foundations, columns, wall etc of size 5 mm wide x 25 mm deep & filling with Polysulphide/ Polyurethine based sealant applied over primer laid as per manufacturer's specification/ drawings etc complete as directed By Engineer In Charge.			
		CUM	111.78	SSR.Item no.26.58
6	Supplying, cleaning, cutting, bending, supporting, binding with 16 SWG soft annealed wire and placing in position steel reinforcement on/at all levels and locations as per drawings, including handling and transport complete for all RCC. Works including supplying & placing concrete cover block etc complete as directed By Engineer In Charge.			
	High yield strength deformed reinforcement bars conforming to IS:1786 10mm Y @200 C/C Both Ways.	M.T.	2.55	SSR.Item no. 26.33

7	Providing and laying 230thk Solid concrete block masonry in sub structure in cement mortar 1:6 using approved quality blocks including scaffolding, curing, raking of joints etc up to FFL etc complete as directed By Engineer In Charge.			
		CUM	49.87	SSR.Item no.29.03
8	Providing and applying internal plaster 12 mm thick in cement mortar 1:4 with neeru finish at all heights & locations for walls, columns, beams etc. including chipping concrete surface, finishing, scaffolding, providing grooves, bands, carvings, mouldings, curing etc complete as directed By Engineer In Charge.			
		SQMT	390.42	SSR.Item no.32.03
9	Providing and applying 20 mm thick exterior sand faced cement plaster in cement mortar 1:3 in two layers for external surfaces including chipping concrete surface, providing, bands, drip moulds, grooves etc. finishing, curing, scaffolding, Waterproofing compound Conplast X4211C (Fosroc) 200 ml per bag of cement etc complete as directed By Engineer In Charge.			
		SQMT	163.54	SSR.Item no.32.11

10	Providing and fixing in position single/double leaf powder coated aluminum glazed door with aluminum frame weighing 2.2 kg/m ,door shutter section with bottom and top rail out of powder coated aluminum section of approved colour, shade, of Jindal or equivalent section weighing 2.2 kg/m with rounded sides,gaskets,all standard accessories like locking arrangement, stoppers, tower bolts, floor spring of approved make with standard pivot fittings, 5 mm thick float glass etc. complete			
		SQMT	25.20	SSR.Item no.39.65
11	Supplying, detailing, and fabricating as per specifications and approved fabrication drawings (which are to be prepared by Contractor and got approved from Engineer), transporting to site and erecting structural steel members for all heights & at all levels including provision of necessary erection bolts, fixing bolts, nuts, washers, cleats, stiffeners, gussets, base plate, and all necessary operations such as but not limited to preheating as per specifications, straightening, bending, cutting, drilling, grinding, machining if specified, welding etc. complete including cleaning, Grinding and removing the welding burr and preparing surface and applying one coat of red oxide zinc chromate primer and one coat of Synthetic Enamel paint after fabrication and second coat of Synthetic Enamel paint after erection, with approved colour, shade and brand etc. including touching up with primer etc. complete, for			
	For Mezzanine Floor	M.T.	2.5	SSR.Item no.23.2
	For Staircase	M.T.	0.9	SSR.Item no.23.2

12	Providing and erecting Galvalume Sheets from approved manufacturers / suppliers (Lloyds/Interarch) of cold rolled steel of yield strength 550 MPa , 0.47 TCT/0.5TCT with metallic coating of 150 gsm Zinc Aluminum organic coating including all accessories like hexa head self drilling screws of size no. 12-14 x 15 mm at every crest with EPDM washers and colour head to match colour of sheeting as per approved fabrication drawings, which are to be supplied by contractor including all sides, end laps as per specifications and sealing of laps with silicon non- hardening type sealant and foam filler wherever required as per directed by engineer including all openings required as per drawings, including testing for leakages etc. complete. laid for area.			
	Colour Coated sheets 0.5 TCT for cladding	SQMT	216.00	SSR.Item no.38.53
13	Providing and applying one coat of approved matching primer and two coats of paint of approved colour and shade and make on interior surfaces including scaffolding, cleaning and preparing surfaces, applying coat of putty etc complete as directed By Engineer In Charge. (for all heights of walls & concrete surfaces)			
	Food Grade Paint	SQMT	650.70	SSR.Item no.36.11
14	Supplying and Fixing Electrical Piping,Ducting, Side Elumination, False Ceiling Light etc..	SQMT	796.42	SSR.Item no. 38.13
			Total	