

# OSAW AGRO INDUSTRIES PVT.LTD.

P.O. Bag 5, Agrosaw Complex, Jagadhri Road, Ambala cantt., Haryana 133001 (India)  
E-mails : agrosaw@agrosaw.com , CIN No. U29211HR2002PTC34843  
Phones : (0091) 171 2699354, 2699167, 2699547 Fax : (0091) 171 2699018  
GSTIN : 06AAACO5198C1ZJ Web : www.agrosaw.com



Our Ref :- SS/Z-1/EQ/18045

Date : Dec.11, 2021

Enq No 35403,

**Bhuseva Farmers Producer Co Ltd**  
NO. 22/1/C, ANGAR WAFAL ROAD,  
KHANDOBACHIWADI, TAL- MOHOL,  
SOLAPUR  
MAHARASHTRA( INDIA )  
Mobile No :9011416975  
Email :  
bhusevafpo@gmail.com

Sub. :- OFFER FOR GRAIN STORAGE AND MATERIAL HANDLING SYSTEM, BASED ON BD.0.75 TON PER CUM.  
Ref :- YOUR DISCUSSION WITH MR. RAJAT PAHWA & MR. GAGANDEEP SINGH

Sr.	PARTICULARS	QTY	UNIT RATE	AMOUNT
<b><u>PART-A (CLEANING &amp; GRADING)</u></b>				
1	<b><u>DUMP HOPPER SIZE 2 MTR X 1 MTR WITH AUTO SLIDE GATE</u></b> Self cleaning type installed beneath floor in a pit so that seed can be fed manually brought in bags. While feeding manually by laborer, adequate number of laborers shall be deployed to ensure feeding of seeds in the intake pit. Made of M.S. Sheet painted to resist corrosion.  Auto slide gate will shut off the discharge of seeds automatically from dump hopper to first bucket elevator in the event of sudden power failure. Auto slide gate will open the gate after the power comes back as soon as 1st V.B. Elevator starts manually. Hence, main purpose of auto slide gate is to prevent damage to motor, chain, belt, sprocket etc. of the elevator. (Rs. Sixty Six Thousand Three Hundred only.)	1 No.	Rs. 66,300	66,300.00
<b><u>SUB-ASSEMBLIES &amp; PARTS</u></b>				
a)	<b><u>AIR COMPRESSOR</u></b> "CLIENT'S SCOPE"  (Rs. -Nil-)	1 No.	Rs.	
2	<b><u>AGROSAW V.B. ELEVATOR CAP. 5 TPH, 8 MDH (SPS)</u></b> All sheet metal components shall be manufactured on CNC machine.  Head casing, boot casing and leg casing made of 2.0 mm, 3.0 mm and 1.6 mm GI. Sheet respectively, spouting and discharge valve made of 1.6 mm GI sheet. Complete with 1.5 H.P. geared motor, service platform, ladder, one length of spouting and all standard features.	1 No.	Rs. 1,99,200	199,200.00

# OSAW AGRO INDUSTRIES PVT.LTD.

P.O. Bag 5, Agrosaw Complex, Jagadhri Road, Ambala cantt., Haryana 133001 (India)  
E-mails : agrosaw@agrosaw.com , CIN No. U29211HR2002PTC34843  
Phones : (0091) 171 2699354, 2699167, 2699547 Fax : (0091) 171 2699018  
GSTIN : 06AAACO5198C1ZJ Web : www.agrosaw.com



Sr.	PARTICULARS	QTY	UNIT RATE	AMOUNT
	<p>Belt shall be NN rubber belt, buckets shall be PU/Nylon/HDPE self cleaning type. Spacers shall be provided in between belt and buckets to prevent damage to seeds. Boot pulley shall be wing type to prevent lodging of seed between belt and pulley. Head pulley shall be rubberised and crowned for improved traction. Sprocket shall be TLB type for easy and quick fitting. Belt speed shall not exceed 1 m/sec. (Rs. One Lakh Ninety Nine Thousand Two Hundred only.)</p>			
3	<p><u>STORAGE BIN CAP 10 TON</u> The sides and 55 degree hoppers bottom are made of 1.6 mm, 2 mm and 3 mm thick G.I. Sheet respectively.  Supporting legs with suitably reinforced bracings made of GI sheet of suitable thickness with 10 mm thick foundation plate are provided for foundation purpose.  All metallic surfaces shall be painted with red oxide primer followed by two coats of enamel paint.  (Rs. Two Lakh Ten Thousand Nine Hundred only.)</p>	1 No.	Rs. 2,10,900	210,900.00
4	<p><u>AGROSAW V.B. ELEVATOR CAP. 5 TPH, 6 MDH (SPS) TO FEED PC-5-NB</u> All sheet metal components shall be manufactured on CNC machine.  Head casing, boot casing and leg casing made of 2.0 mm, 3.0 mm and 1.6 mm GI. Sheet respectively, spouting and discharge valve made of 1.6 mm GI sheet. Complete with 1.5 H.P. geared motor starter and switch, service platform, ladder, one length of spouting and all standard features.  Belt shall be NN rubber belt, buckets shall be PU/Nylon/HDPE self cleaning type. Spacers shall be provided in between belt and buckets to prevent damage to seeds. Boot pulley shall be wing type to prevent lodging of seed between belt and pulley. Head pulley shall be rubberised and crowned for improved traction. Sprocket shall be TLB type for easy and quick fitting. Belt speed shall not exceed 1 m/sec. (Rs. One Lakh Eighty Three Thousand Two Hundred only.)</p>	1 No.	Rs. 0	0

# OSAW AGRO INDUSTRIES PVT.LTD.

P.O. Bag 5, Agrosaw Complex, Jagadhri Road, Ambala cantt., Haryana 133001 (India)  
 E-mails : agrosaw@agrosaw.com , CIN No. U29211HR2002PTC34843  
 Phones : (0091) 171 2699354, 2699167, 2699547 Fax : (0091) 171 2699018  
 GSTIN : 06AAACO5198C1ZJ Web : www.agrosaw.com



Sr.	PARTICULARS	QTY	UNIT RATE	AMOUNT	
5	<p><b><u>AGROSAW SEED CLEANER MODEL PC-5-NB</u></b>                      Cap.: Upto 6.5 Tons/Hr. based on wheat at 12% moisture content &amp; 20% impurities.</p> <p>It is totally made of steel with structural frame work.Compact &amp; sturdy construction. Designed for efficient cleaning of various crop seeds, such as wheat, paddy, bajra, maize, sunflower, soyabean, gram, pulses, vegetable seeds, oilseeds, fodder crop seeds etc.</p> <p>It has two flat oscillating screens, perforation cleaning of screens by nylon brush, single aspiration, variable shoe shake, variable angle for top screen, 4 HP motor for blower and 1.5 HP motor for screen deck and nylon brush drive, 440 V, Siemens/Crompton/Rotomotive/Equivalent, Screen size : 122 x 180 cm. regulated feed hopper with roller, dynamically balanced fan air chamber screen deck and spouts are self cleaning type. O.A. Size of Machine: 225 x180x 235 cms. LWH.</p> <p>Complete with electric motors and fitted with one set of screens and all other standard features.                      (Rs. Five Lakh Twenty Five Thousand Seven Hundred only.)  <b><u>SUB-ASSEMBLIES &amp; PARTS</u></b></p> <p>a) <b><u>PC-5 AIR TRUNK (G.I.)(PC5-AT-00)</u></b>                      1 meter long both ends flanged.                      (Rs. Nine Thousand Six Hundred only.)</p> <p>b) <b><u>CYCLONE DUST COLLECTOR FOR PC-5-NB</u></b>                      (Rs. Eleven Thousand Eight Hundred only.)</p>	1 No.	Rs.	0	0
6	<p><b><u>AGROSAW V.B. ELEVATOR CAP. 5 TPH. 5 MDH (SPS)</u></b>                      All sheet metal components shall be manufactured on CNC machine.</p> <p>Head casing, boot casing and leg casing made of 2.0 mm, 3.0 mm and 1.6 mm GI. Sheet respectively, spouting and discharge valve made of 1.6 mm GI sheet. Complete with 1.5 H.P. geared motor starter and switch, service platform, ladder, one length of spouting and all</p>	1 No.	Rs.	1,75,300	175,300.00

# OSAW AGRO INDUSTRIES PVT.LTD.

P.O. Bag 5, Agrosaw Complex, Jagadhri Road, Ambala cantt., Haryana 133001 (India)  
 E-mails : agrosaw@agrosaw.com , CIN No. U29211HR2002PTC34843  
 Phones : (0091) 171 2699354, 2699167, 2699547 Fax : (0091) 171 2699018  
 GSTIN : 06AAACO5198C1ZJ Web : www.agrosaw.com



Sr.	PARTICULARS	QTY	UNIT RATE	AMOUNT
-----	-------------	-----	-----------	--------

standard features.

Belt shall be NN rubber belt, buckets shall be PU/Nylon/HDPE self cleaning type. Spacers shall be provided in between belt and buckets to prevent damage to seeds. Boot pulley shall be wing type to prevent lodging of seed between belt and pulley. Head pulley shall be rubberised and crowned for improved traction. Sprocket shall be TLB type for easy and quick fitting. Belt speed shall not exceed 1 m/sec.  
 (Rs. One Lakh Seventy Five Thousand Three Hundred only.)



7	<b><u>AGROSAW SEED GRADER MODEL SG3 - II</u></b> Capacity : 4-5 Tons/Hr. based on wheat at 12% moisture content and 10% impurities.	1 No.	Rs. 6,47,200	647,200.00
---	----------------------------------------------------------------------------------------------------------------------------------------	-------	--------------	------------

Compact & sturdy construction. Designed for efficient grading of various crop seeds, such as wheat, paddy, barley, bajra, maize, sunflower, soyabean, gram, pulses, vegetable seeds, oilseeds, fodder crop seeds etc.

It has three flat oscillating screens, perforation cleaning of top screen by beaters, middle & bottom screen by rubber balls, two air aspirations, variable shoe shake, 7.5 H.P. motor for blower and 2 H.P. motor for sieve cradle of Siemens/Crompton/Rotomotive/ equivalent for operation on 440 V, 3 Ph., 50 c/s AC supply. Screen size of Top, Middle & Bottom Screens : 142 x 178 cms. (WxL), regulated feed hopper with feed roller, dynamically balanced fan, air chamber screen deck and spouts are self cleaning.

Complete with electric motors, starter, switch, fitted with one set of screens and other standard features.

(Rs. Six Lakh Forty Seven Thousand Two Hundred only.)

### **SUB-ASSEMBLIES & PARTS**

a)	<b><u>G.I. SPIRAL DUCTING FOR SG-3</u></b>	3 No.	Rs. 4,100	12,300
----	--------------------------------------------	-------	-----------	--------

(Rs. Twelve Thousand Three Hundred only.)

# OSAW AGRO INDUSTRIES PVT.LTD.

P.O. Bag 5, Agrosaw Complex, Jagadhri Road, Ambala cantt., Haryana 133001 (India)  
 E-mails : agrosaw@agrosaw.com , CIN No. U29211HR2002PTC34843  
 Phones : (0091) 171 2699354, 2699167, 2699547 Fax : (0091) 171 2699018  
 GSTIN : 06AAACO5198C1ZJ Web : www.agrosaw.com



Sr.	PARTICULARS	QTY	UNIT RATE	AMOUNT
	b) <u>CYCLONE DUST COLLECTOR FOR SG-3</u>	1 No.	Rs. 89,400	89,400
	(Rs. Eighty Nine Thousand Four Hundred only.)			
8	<u>AGROSAW V.B. ELEVATOR CAP. 5 TPH, 4.5 MDH (SPS) TO FEED D-6-NE</u> All sheet metal components shall be manufactured on CNC machine.  Head casing, boot casing and leg casing made of 2.0 mm, 3.0 mm and 1.6 mm GI. Sheet respectively, spouting and discharge valve made of 1.6 mm GI sheet. Complete with 1.5 H.P. geared motor starter and switch, service platform, ladder, one length of spouting and all standard features.  Belt shall be NN rubber belt, buckets shall be PU/Nylon/HDPE self cleaning type. Spacers shall be provided in between belt and buckets to prevent damage to seeds. Boot pulley shall be wing type to prevent lodging of seed between belt and pulley. Head pulley shall be rubberised and crowned for improved traction. Sprocket shall be TLB type for easy and quick fitting. Belt speed shall not exceed 1 m/sec. (Rs. One Lakh Seventy Two Thousand Seven Hundred only.)	1 No.	Rs. 1,72,700	172,700.00
9	<u>AGROSAW DESTONER MODEL D-6-NE</u> Capacity : 3-6 Tons/hr. (Based on Wheat)  It is meant for removing foreign impurities like stones, metal pieces, glass pieces, mud balls etc. from grains and seeds of all types and any granular material like seeds, grains, pulses, cereals etc.  Negative pressure type, compact and sturdy steel channel frame, dynamically balanced centrifugal fan with adjustable air control variable oscillation speed of deck, deck size : 1220 x 741 mm, variable inclination angle of deck and regulated feeding.  Complete with 0.5 HP vibratory motor, fan with 7.5 HP motor, suitable for 440 V, 50 Hz, 3 Ph. AC Supply, fitted with deck for wheat.	1 No.	Rs. 3,35,600	335,600.00
	NOTE: <u>Since destoner works on the principal of difference in</u>			

# OSAW AGRO INDUSTRIES PVT.LTD.

P.O. Bag 5, Agrosaw Complex, Jagadhri Road, Ambala cantt., Haryana 133001 (India)  
 E-mails : agrosaw@agrosaw.com , CIN No. U29211HR2002PTC34843  
 Phones : (0091) 171 2699354, 2699167, 2699547 Fax : (0091) 171 2699018  
 GSTIN : 06AAACO5198C1ZJ Web : www.agrosaw.com



Sr.	PARTICULARS	QTY	UNIT RATE	AMOUNT
	<p><u>weight, therefore stones, mud balls or any heavy impurity having same weight as of grains can not be separated with any destoner. These impurities shall be separated effectively if the weight difference between stone/mud balls is 20% and more than the weight of grains.</u></p> <p>(Rs. Three Lakh Thirty Five Thousand Six Hundred only.)</p> <p><b><u>SUB-ASSEMBLIES &amp; PARTS</u></b></p>			
a)	<p><u>G.I.SPIRAL DUCTING FOR D-6-NE</u>                      1 meter long both ends flanged.                      (Rs. Twelve Thousand Eight Hundred only.)</p>	4 No.	Rs. 3,200	12,800
b)	<p><u>DUST COLLECTOR FOR DESTONER D-6-NE</u>                      (Rs. Eighty Eight Thousand One Hundred only.)</p>	1 No.	Rs. 88,100	88,100
c)	<p><u>BLOWER WITH BLOWER FRAME</u>                      (Rs. One Lakh Twenty Six Thousand Three Hundred only.)</p>	1 No.	Rs. 1,26,300	1,26,300
d)	<p><u>FOUNDATION FRAME</u>                      (Rs. Twenty Thousand Eight Hundred only.)</p>	1 No.	Rs. 20,800	20,800
10	<p><u>AGROSAW V.B. ELEVATOR CAP. 5 TPH TO FEED MRS-4</u>                      All sheet metal components shall be manufactured on CNC machine.</p> <p>Head casing, boot casing and leg casing made of 2.0 mm, 3.0 mm and 1.6 mm GI. Sheet respectively, spouting and discharge valve made of 1.6 mm GI sheet. Complete with 1.5 H.P. geared motor, service platform, ladder, one length of spouting and all standard features.</p> <p>Belt shall be NN rubber belt, buckets shall be PU/Nylon/HDPE self cleaning type. Spacers shall be provided in between belt and buckets to prevent damage to seeds. Boot pulley shall be wing type to prevent lodging of seed between belt and pulley. Head pulley shall be rubberised and crowned for improved traction. Sprocket shall be TLB type for easy and quick fitting. Belt speed shall not exceed 1 m/sec.                      (Rs. One Lakh Ninety Five Thousand only.)</p>	1 No.	Rs. 1,95,000	195,000.00

# OSAW AGRO INDUSTRIES PVT.LTD.

P.O. Bag 5, Agrosaw Complex, Jagadhri Road, Ambala cantt., Haryana 133001 (India)  
 E-mails : agrosaw@agrosaw.com , CIN No. U29211HR2002PTC34843  
 Phones : (0091) 171 2699354, 2699167, 2699547 Fax : (0091) 171 2699018  
 GSTIN : 06AAACO5198C1ZJ Web : www.agrosaw.com



Sr.	PARTICULARS	QTY	UNIT RATE	AMOUNT
11	<p><b><u>AGROSAW MAGNETIC ROLL SEPARATOR CAP. 4 TPH</u></b>                      For separating ferrous mud balls.</p> <p>Cap: 4 TPH based on wheat</p> <p>Magnetic &amp; non magnetic roll:100x1500mm DxL                      Motor for roll : 1 HP                      Motor for vibratory feeder : 0.5 HP                      Hopper size: 1400x500x500 mm LxWxH</p> <p>FEATURES:                      * Robust machine of all steel construction with M.S. Square pipe 40x40 mm, 75x38 mm ISMC.                      * High intensity rare earth Nd-Feb, Grade N-45 having 13000 gauss value                      * Feeding Hopper equipped with drawer magnet having 5000 gauss value.</p> <p>Completely closed construction.</p> <p>Machine is supplied complete with 1 HP motor for magnetic roller and 0.5 HP vibratory motor for vibratory feeder. Suitable for 415V 50 Hz 3 phase supply. Motor make Siemens/Crompton/ABB/Rotomotive.</p> <p>(Rs. Four Lakh Sixty Thousand Two Hundred only.)</p> <p><b><u>SUB-ASSEMBLIES &amp; PARTS</u></b></p> <p>a) <b><u>EXTENDED FOUNDATION FRAME FOR MRS-4</u></b></p> <p>(Rs. Sixty One Thousand Eight Hundred only.)</p>	1 No.	Rs. 4,60,200	460,200.00
12	<p><b><u>AGROSAW SEED GRAVITY SEPARATOR MODEL G-6-P II</u></b>                      Capacity: 6 Tons/Hr. based on wheat and depending upon grading quality to be achieved.</p> <p>It is meant for removing impurities on specific density principle, grains same in size but different in weight shall be separated. Three or more grades can be taken. Suitable for all types of grains, seeds and granular product.</p> <p>Compact &amp; sturdy steel channel frame with high quality wooden rectangular deck, deck size 1150 x 3100 mm, (WxL) mounted on teflon bushings dynamically balanced fans (7Nos) with individual</p>	1 No.	Rs. 5,35,700	535,700.00

# OSAW AGRO INDUSTRIES PVT.LTD.

P.O. Bag 5, Agrosaw Complex, Jagadhri Road, Ambala cantt., Haryana 133001 (India)  
 E-mails : agrosaw@agrosaw.com , CIN No. U29211HR2002PTC34843  
 Phones : (0091) 171 2699354, 2699167, 2699547 Fax : (0091) 171 2699018  
 GSTIN : 06AAACO5198C1ZJ Web : www.agrosaw.com



Sr.	PARTICULARS	QTY	UNIT RATE	AMOUNT
	<p>adjustable air control, variable oscillation with the help of variable frequency drive, lengthwise and sidewise inclination of decking, has hydraulic system for cleaning of deck, regulated feeding, built in air filters.</p> <p>Complete with big hopper of 500 Kg capacity, electric motor of 10 HP for fans and 3 HP for deck, 440 V Siemens/Crompton/Rotomotive/Equiv. standard make and other standard features.                      (Rs. Five Lakh Thirty Five Thousand Seven Hundred only.)</p> <p><b><u>SUB-ASSEMBLIES &amp; PARTS</u></b></p>			
	<p>a) <u>SURGE HOPPER (G.I.) FOR G-6PII 650 KG</u></p> <p>(Rs. Fifty Three Thousand Two Hundred only.)</p>	1 No.	Rs. 53,200	53,200
13	<p><u>AGROSAW V.B. ELEVATOR CAP. 5 TPH. 10 MDH (SPS)</u>                      All sheet metal components shall be manufactured on CNC machine.</p> <p>Head casing, boot casing and leg casing made of 2.0 mm, 3.0 mm and 1.6 mm GI. Sheet respectively, spouting and discharge valve made of 1.6 mm GI sheet. Complete with 1.5 H.P. geared motor, service platform, ladder, one length of spouting and all standard features.</p> <p>Belt shall be NN rubber belt, buckets shall be PU/Nylon/HDPE self cleaning type. Spacers shall be provided in between belt and buckets to prevent damage to seeds. Boot pulley shall be wing type to prevent lodging of seed between belt and pulley. Head pulley shall be rubberised and crowned for improved traction. Sprocket shall be TLB type for easy and quick fitting. Belt speed shall not exceed 1 m/sec.                      (Rs. Two Lakh Fifteen Thousand Three Hundred only.)</p>	1 No.	Rs. 2,15,300	215,300.00
14	<p><u>COLOR SORTER</u>                      " CLIENT SCOPE "  <b><u>SUB-ASSEMBLIES &amp; PARTS</u></b></p>	1 No.		
	<p>a) <u>UPS CVCF 5KVA</u>                      "CLIENT'S SCOPE"                      (Rs. -Nil-)</p>	1 No.	Rs.	

# OSAW AGRO INDUSTRIES PVT.LTD.

P.O. Bag 5, Agrosaw Complex, Jagadhri Road, Ambala cantt., Haryana 133001 (India)  
 E-mails : agrosaw@agrosaw.com , CIN No. U29211HR2002PTC34843  
 Phones : (0091) 171 2699354, 2699167, 2699547 Fax : (0091) 171 2699018  
 GSTIN : 06AAACO5198C1ZJ Web : www.agrosaw.com



Sr.	PARTICULARS	QTY	UNIT RATE	AMOUNT
b)	<u>OIL FREE DRY AIR COMPRESSOR 25 HP TO OPERATE COLOR SORTER</u> "CLIENT'S SCOPE" (Rs. -Nil-)	1 No.	Rs.	
c)	<u>RAISED PLATFORM STRUCTURE FOR COLOR SORTER</u> M.S. Rigid Structure. Consist of M.S. Channels, angles, pipes of ISI mark with only slippery checkered sheet on the surface of platform with clear height for manual walkway. Complete with railing with vertical support & ladder. (Rs. Three Lakh Seventy Two Thousand Nine Hundred only.)	1 No.	Rs. 3,72,900	3,72,900
d)	<u>CABIN FOR COLOR SOTEX</u> (Rs. Two Lakh Fourteen Thousand Six Hundred only.)	1 No.	Rs. 2,14,600	2,14,600
e)	<u>AIR CONDITIONER 1.5T</u> "CLIENT'S SCOPE" (Rs. -Nil-)	1 No.	Rs.	
f)	<u>CONTROL PANEL FOR COLOR SORTER</u> (Rs. Forty Four Thousand only.)	1 No.	Rs. 44,000	44,000
g)	<u>TECHNOLOGICAL CONNECTIONS FOR COLOR SORTER</u> (Rs. Two Lakh Twelve Thousand Three Hundred only.)	1 No.	Rs. 2,12,300	2,12,300
h)	<u>PLUMBING JOB FOR COLOR SORTER</u> (Rs. Forty Nine Thousand Five Hundred only.)	1 No.	Rs. 49,500	49,500
i)	<u>CENTRIFUGAL BLOWER 1 HP FOR COLOR SORTER</u> (Rs. Forty Four Thousand Two Hundred only.)	1 No.	Rs. 44,200	44,200
15	<u>AGROSAW V.B. ELEVATOR CAP. 2TPH, 9.5 MDH (SPS) FOR RECYCLING</u>	2 No.	Rs. 1,85,800	371,600.00

# OSAW AGRO INDUSTRIES PVT.LTD.

P.O. Bag 5, Agrosaw Complex, Jagadhri Road, Ambala cantt., Haryana 133001 (India)  
 E-mails : agrosaw@agrosaw.com , CIN No. U29211HR2002PTC34843  
 Phones : (0091) 171 2699354, 2699167, 2699547 Fax : (0091) 171 2699018  
 GSTIN : 06AAACO5198C1ZJ Web : www.agrosaw.com



Sr.	PARTICULARS	QTY	UNIT RATE	AMOUNT
	<p>All sheet metal components shall be manufactured on CNC machine.</p> <p>Head casing, boot casing and leg casing made of 2.0 mm, 3.0 mm and 1.6 mm GI Sheet respectively, spouting and discharge valve made of 1.6 mm GI sheet. Complete with 1 H.P. geared motor starter and switch, service platform, ladder, one length of spouting and all standard features.</p> <p>Belt shall be NN rubber belt, buckets shall be PU/Nylon/HDPE self cleaning type. Spacers shall be provided in between belt and buckets to prevent damage to seeds. Boot pulley shall be wing type to prevent lodging of seed between belt and pulley. Head pulley shall be rubberised and crowned for improved traction. Sprocket shall be TLB type for easy and quick fitting. Belt speed shall not exceed 1 m/sec.                      (Rs. Three Lakh Seventy One Thousand Six Hundred only.)</p>			
16	<p><u>AGROSAW V.B. ELEVATOR TO FEED REJECTION BIN</u>                      All sheet metal components shall be manufactured on CNC machine.</p> <p>Head casing, boot casing and leg casing made of 2.0 mm, 3.0 mm and 1.6 mm GI. Sheet respectively, spouting and discharge valve made of 1.6 mm GI sheet. Complete with 1.5 H.P. geared motor starter and switch, service platform, ladder, one length of spouting and all standard features.</p> <p>Belt shall be NN rubber belt, buckets shall be PU/Nylon/HDPE self cleaning type. Spacers shall be provided in between belt and buckets to prevent damage to seeds. Boot pulley shall be wing type to prevent lodging of seed between belt and pulley. Head pulley shall be rubberised and crowned for improved traction. Sprocket shall be TLB type for easy and quick fitting. Belt speed shall not exceed 1 m/sec.                      (Rs. One Lakh Seventy Five Thousand Three Hundred only.)</p>	1 No.	Rs. 1,75,300	175,300.00
17	<p><u>AGROSAW REJECTION BIN 2 TONS</u>                      Capacity : 2 Ton on wheat</p> <p>The sides and 55 degree hopped bottom are made</p>	1 No.	Rs. 93,700	93,700.00

# OSAW AGRO INDUSTRIES PVT.LTD.

P.O. Bag 5, Agrosaw Complex, Jagadhri Road, Ambala cantt., Haryana 133001 (India)  
 E-mails : agrosaw@agrosaw.com , CIN No. U29211HR2002PTC34843  
 Phones : (0091) 171 2699354, 2699167, 2699547 Fax : (0091) 171 2699018  
 GSTIN : 06AAACO5198C1ZJ Web : www.agrosaw.com



Sr.	PARTICULARS	QTY	UNIT RATE	AMOUNT
	of 1.6 mm and 2 mm thick G I Sheet respectively. M.S. Pipe for supporting legs with 10 mm thick foundation plate, suitable M.S. Pipe bracing. Equipped with manually operated discharge gate, transparent sheet window for seeing the seed level in the bin. (Rs. Ninety Three Thousand Seven Hundred only.)			
18	<p><u>AGROSAW V.B. ELEVATOR (SPS) CAP. 5 TPH 4.5 MDH TO FEED SM-II-3GF</u>                      All sheet metal components shall be manufactured on CNC machine.</p> <p>Head casing, boot casing and leg casing made of 2.0 mm, 3.0 mm and 1.6 mm GI. Sheet respectively. Spouting shall be made of 2 mm M.S. Sheet.</p> <p>Spouting, spout sections, discharge valve, ladder, service platform, boot plate, take up unit, hopper with grating and feed control gate shall be made of M.S. silver painted.</p> <p>Belt shall be NN 315/3 (3 ply), buckets shall be PU/Nylon/HDPE, self cleaning type. Spacers shall be provided in between belt and buckets to prevent damage to seeds. Boot pulley shall be wing type to prevent lodging of seed between belt and pulley. Head pulley shall be rubberised and crowned for improved traction. Sprocket shall be TLB type for easy and quick fitting. Belt speed shall not exceed 1 m/sec.</p> <p>Complete with 1.5 HP geared motor and other standard features.                      (Rs. One Lakh Seventy Two Thousand Seven Hundred only.)</p>	1 No.	Rs. 1,72,700	172,700.00
19	<p><u>AGROSAW SEED GRADER MODEL SEED MASTER-II-3-GF WITH FOUNDATION FRAME</u>                      Capacity: 3 TPH based on wheat at 12% moisture content and 10% impurities.</p> <p>Machine is suitable for efficient Cleaning and grading of seeds of all crops such as Wheat, Paddy, Maize, Millets, Sunflower, Soybean, Barley, Oil Seeds, Vegetable Seeds, Coffee Seeds, pulses and various spices etc.</p> <p>SPECIFICATION:                      No. of Screens : Three (flat, oscillating type)(5 section arranged in 3 layers)                      No. of Scalping : One</p>	1 No.	Rs. 6,25,000	625,000.00

# OSAW AGRO INDUSTRIES PVT.LTD.

P.O. Bag 5, Agrosaw Complex, Jagadhri Road, Ambala cantt., Haryana 133001 (India)  
 E-mails : agrosaw@agrosaw.com , CIN No. U29211HR2002PTC34843  
 Phones : (0091) 171 2699354, 2699167, 2699547 Fax : (0091) 171 2699018  
 GSTIN : 06AAACO5198C1ZJ Web : www.agrosaw.com



Sr.	PARTICULARS	QTY	UNIT RATE	AMOUNT
-----	-------------	-----	-----------	--------

No. of Scalping : One  
 No. of Grading : Two  
 Size of each Screen : Top:105 x 80 cm (WxL)  
                                   Middle:105x160cm (WxL)  
                                   Bottom:105x160cm(WxL)  
 Total Screening Area : 4.2 square meter  
 Screen Inclination : Fixed  
 Screen perforation  
 Cleaning device : Rubber Balls  
 Oscillating speed of  
 Screen deck : Variable  
 No. of aspirations : Two  
 Electric Drive : Blower - 4 HP  
                                   Cradle - 1 HP  
                                   Rejects - 0.5 HP  
                                   440V, 3 Ph., 50 c/s.,  
                                   A.C. Supply.  
 Overall dimension : 217x190x175 cms  
                                   (L x W x H)

The unit is supplied complete with electric motor, panel, fitted with one set of screen and other standard features.  
 (Rs. Six Lakh Twenty Five Thousand only.)

### **SUB-ASSEMBLIES & PARTS**

a)	<u>DUST COLLECTOR FOR SM-II-3GF</u>	1 No.	Rs. 91,100	91,100
	(Rs. Ninety One Thousand One Hundred only.)			
b)	<u>G.I.SPIRAL DUCTING</u>	3 No.	Rs. 3,200	9,600
	1 meter long both ends flanged. (Rs. Nine Thousand Six Hundred only.)			
20	<u>AGROSAW V.B. ELEVATOR CAP. 5 TPH, 4.5 MDH (SPS) TO FEED POLISHER</u>	1 No.	Rs. 1,72,700	172,700.00

All sheet metal components shall be manufactured on CNC machine.

Head casing, boot casing and leg casing made of 2.0 mm, 3.0 mm and 1.6 mm GI. Sheet respectively, spouting and discharge valve made of 1.6 mm GI sheet. Complete with 1.5 H.P. geared motor starter and switch, service platform, ladder, one length of spouting and all standard features.

Belt shall be NN rubber belt, buckets shall be PU/Nylon/HDPE self cleaning type. Spacers shall be provided in between belt and buckets to prevent

# OSAW AGRO INDUSTRIES PVT.LTD.

P.O. Bag 5, Agrosaw Complex, Jagadhri Road, Ambala cantt., Haryana 133001 (India)  
 E-mails : agrosaw@agrosaw.com , CIN No. U29211HR2002PTC34843  
 Phones : (0091) 171 2699354, 2699167, 2699547 Fax : (0091) 171 2699018  
 GSTIN : 06AAACO5198C1ZJ Web : www.agrosaw.com



Sr.	PARTICULARS	QTY	UNIT RATE	AMOUNT
	damage to seeds. Boot pulley shall be wing type to prevent lodging of seed between belt and pulley. Head pulley shall be rubberised and crowned for improved traction. Sprocket shall be TLB type for easy and quick fitting. Belt speed shall not exceed 1 m/sec. (Rs. One Lakh Seventy Two Thousand Seven Hundred only.)			
21	<u>POLISHER</u> "CLIENT'S SCOPE"	1 No.		
22	<u>AGROSAW V.B. ELEVATOR CAP. 5 TPH. 10 MDH (SPS) TO SILO 25TONS</u> All sheet metal components shall be manufactured on CNC machine.  Head casing, boot casing and leg casing made of 2.0 mm, 3.0 mm and 1.6 mm GI. Sheet respectively, spouting and discharge valve made of 1.6 mm GI sheet. Complete with 1.5 H.P. geared motor starter and switch, service platform, ladder, one length of spouting and all standard features.  Belt shall be NN rubber belt, buckets shall be PU/Nylon/HDPE self cleaning type. Spacers shall be provided in between belt and buckets to prevent damage to seeds. Boot pulley shall be wing type to prevent lodging of seed between belt and pulley. Head pulley shall be rubberised and crowned for improved traction. Belt tensioning with bakelite slide. Sprocket shall be TLB type for easy and quick fitting. Belt speed shall not exceed 1 m/sec. (Rs. Two Lakh Thirty Five Thousand Five Hundred only.)	1 No.	Rs. 2,35,500	235,500.00
23	<u>HOPPER BOTTOM SQUARE SILO 25 MT</u> Square Silo suitable for storage of seed/grains  capacity 25 Tons on BD 750 kg/cubic meter. The silo has following features.  * Sidewall & hopper bottom made of 120 GSM G.I. Sheet. * Supporting structure is made of G.I. Sheet * Hopper section is equipped with manually control discharge gate. * Sheet thickness of hopper bottom is upto 3mm	1 No.	Rs. 4,98,000	498,000.00

# OSAW AGRO INDUSTRIES PVT.LTD.

P.O. Bag 5, Agrosaw Complex, Jagadhri Road, Ambala cantt., Haryana 133001 (India)  
 E-mails : agrosaw@agrosaw.com , CIN No. U29211HR2002PTC34843  
 Phones : (0091) 171 2699354, 2699167, 2699547 Fax : (0091) 171 2699018  
 GSTIN : 06AAACO5198C1ZJ Web : www.agrosaw.com



Sr.	PARTICULARS	QTY	UNIT RATE	AMOUNT
	<p>Sheet thickness of side wall is 3.0mm/2.0mm /1.6 mm.                      * Sheet thickness of top cover is 2 mm.                      * Discharge Ht. is <b>1490 mm</b> from ground level.                      * All nuts &amp; bolts are of good quality &amp; G.I. coated, with rubber/neoprone washer                      * M.S. component duly redoxide.                      (Rs. Nine Lakh Ninety Six Thousand only.)</p>			
24	<p><b><u>TECHNOLOGICAL CONNECTIONS</u></b>                      Like pit cover, seed diverting chutes, electric discharge gate etc.                      (Rs. Three Lakh Ninety Five Thousand only.)</p>	1 No.	Rs. 3,95,000	395,000.00
25	<p><b><u>ELECTRIC CONTROL PANEL</u></b>                      The panel shall be equipped with main on/off switch to allow the machines to be powered either from the generator or main supply, voltmeter, ammeter, phase indicators, motor starters with protective relays and fuses, 2 Nos. 15 Amp sockets of 220V single phase are provided for ancillary equipment/lights etc.                       All motors fitted with the machines shall be tropically rated totally enclosed fan cooled type and current protecting. Suitable for 415 V, 50 Hz, 3 Phase, AC Supply.                       (Rs. Five Lakh Forty One Thousand Six Hundred only.)</p>	1 No.	Rs. 5,41,600	541,600.00
26	<p><b><u>INSTALLATION &amp; COMISSIONING CHARGES (WITHOUT CIVIL WORK)</u></b>                      SUPPLIER SCOPE (AGROSAW)                      1.On receipt of purchase order we send Engineer at site to take measurement of building to know suitability for installation of plant.                      2.After site visit, we prepare machine layout showing raw seed intake, clean seed out, position of dust collector, height of elevators etc. &amp; send it for approval to customer.                      3.On the basis of approved machine layout by purchaser, we prepare civil foundation drawing.                      4.Opening of packing boxes at site.                      5.Assembly &amp; Erection of Equipment.                      6.To arrange unskilled labour required for assembly &amp; erection of plant.                      7.Electrical connection to all equipment from the supplied electrical control panel. Electric control panel shall be installed at maximum distance up to 5m from the machine, distance beyond 5m shall be to the customer account, laying</p>	1 No.	Rs. 7,50,000	750,000.00

# OSAW AGRO INDUSTRIES PVT.LTD.

P.O. Bag 5, Agrosaw Complex, Jagadhri Road, Ambala cantt., Haryana 133001 (India)  
 E-mails : agrosaw@agrosaw.com , CIN No. U29211HR2002PTC34843  
 Phones : (0091) 171 2699354, 2699167, 2699547 Fax : (0091) 171 2699018  
 GSTIN : 06AAACO5198C1ZJ Web : www.agrosaw.com



Sr.	PARTICULARS	QTY	UNIT RATE	AMOUNT
	<p>of cables shall be under ground in PVC pipes.</p> <p>8.To provide electric cables, electric items required for electrification of complete plant.</p> <p>9.Air ducting, delivery chutes &amp; any other item required to complete the machine.</p> <p>10.Commissioning &amp; Trial of machines with the product.</p> <p>11.Training to user's staff for proper maintenance, adjustment &amp; operation of the machine.</p> <p><b>CUSTOMER/PURCHASER SCOPE</b></p> <p>1.To unload &amp; to transport the equipment from unloading point to installation site.</p> <p>2.Proper building &amp; space for installation &amp; commissioning of the machines/plants &amp; any other civil work beyond supplier scope. Installation on unfinished/incomplete flooring shall not be done by Agrosaw.</p> <p>3.Electric cables from main grid to main control panel of the plant with proper earthing.</p> <p>4.Facility to work at site after office hours/holidays, if required.</p> <p>5.Desired height platform for fitting of dust collector outside the building.</p> <p>6.To provide warehouse to store equipment which need protection from bad weather conditions &amp; thefts etc.</p> <p>7.To arrange electric connection at site to run tools &amp; equipment required for installation &amp; commissioning of the project.</p> <p>8.To arrange water for civil works &amp; safe drinking water for work force to be engaged to install &amp; commission the project.</p> <p>9.To provide raw material (seed, grain) for trial purpose.</p> <p>10.Licenses,permissions &amp; necessary authorization for installation if required.</p> <p>11.To arrange operator/Responsible Person for Operational/Maintenance works.</p> <p>12. Any change in the layout after the start of installation shall be to the customer account.</p> <p>13.If customer wants cable to be laid on cable trays and or in trenches then expenditure on this shall be to customer account.</p> <p>14.To arrange widening of gate height &amp; width for machine to enter in the building &amp; after machines are shifted inside godown, then customer shall arrange the repair at his cost.</p> <p>15.Noise reducing system, Fire fighting, General electric installation, Work contract tax is in the scope of the customer.</p> <p>16.To arrange civil work through mason for cabling &amp; V.B. Elevator pits, machine foundation pit etc.</p> <p>17.Crane/Fork lift etc. shall be arranged by the purchaser. (Rs. Seven Lakh Fifty Thousand only.)</p>			
27	<p><b><u>ELECTRIFICATION OF PLANT</u></b></p> <p>Power cables, glands &amp; accessories for connecting machines motor to control panel only. Cables shall be</p>	1 No.	Rs. 1,65,000	165,000.00

# OSAW AGRO INDUSTRIES PVT.LTD.

P.O. Bag 5, Agrosaw Complex, Jagadhri Road, Ambala cantt., Haryana 133001 (India)  
E-mails : agrosaw@agrosaw.com , CIN No. U29211HR2002PTC34843  
Phones : (0091) 171 2699354, 2699167, 2699547 Fax : (0091) 171 2699018  
GSTIN : 06AAACO5198C1ZJ Web : www.agrosaw.com



Sr.	PARTICULARS	QTY	UNIT RATE	AMOUNT
	copper unarmoured, Anti termite type. (Rs. One Lakh Sixty Five Thousand only.)			
	Sub Total			89,12,400.00
	DISCOUNT			2,228,100.00
				66,84,300.00
	<b>Total</b>			<b>66,84,300.00</b>

## TERMS & CONDITIONS

- 1 PRICES: Our prices are Ex-works, Ambala Cantt. Freight to pay.
- 2 PAINT: All the metallic parts of machines shall be painted in "PU" paint as standard supply in the quoted price.
- 3 Transit Insurance shall be charged extra @ 0.5% on the 110% invoice value Plus GST as applicable at the time of supply.
- 4 Unloading of equipment at site shall be arranged by the buyer at his own risk and cost.
- 5 GST: It shall be charged extra as applicable at the time of supply. At present rate of GST is as follows:-  
Our GST No. 06AAACO5198C1ZJ  
@ 5% on Seed/Grain Cleaners & Parts. @ 5% on Seed Graders & Parts.  
@ 5% on Seed Gravity Separators & Parts. @ 5% on De-Stoners & Parts.  
@ 18% on V.B. Elevator/Conveyor & Parts. @ 18% on Silo & Parts.  
@ 5% on Color Sorter. @ 18% on Electric Control Panel.
- 6 If there is any change in the rate of taxes and/or imposition of any new taxes at the time of supply that shall be to buyer's account.
- 7 Validity: Our rates shall remain valid for 60 days from the date of our offer, afterward subject to confirmation.
- 8 Delivery: The equipment shall be despatched within 6 to 8 weeks from Ambala Cantt after receipt of your technically & commercially clear confirmed order.  
NOTE: However, because of on going Covid-19 Pandemic, we can honour the delivery schedule if the situation normalizes & we are able to undertake normal manufacturing cycle.
- 9 Warranty: 12 Calendar months from the date of despatch against any manufacturing defect and/or bad workmanship.
- 10 Payment: 40% payment advance alongwith your order and balance 60% payment before dispatch of machines. All the payments by Bank Draft in favour of OSAW AGRO INDUSTRIES PVT. LTD. payable at any nationalised Bank at Ambala Cantt. All Bank charges shall be to buyer's account.  
CC ACCOUNT No. 3887 0087 00 00 2289 IFSC CODE: PUNB0388700
- 11 Service Tax @ 18% shall be charged extra on erection & commissioning charges separately.
- 12 For all disputes the jurisdiction would be Ambala only.
- 13 If installation of machine is to be done through Chemical Anchoring than floor must be RCC (Reinforced cement concrete) with minimum thickness of 150mm over 100mm PCC ( Plain cement concrete ) on compact soil.
- 14 If the depth of water table is less than the depth of Elevator pit/foundation, chances of water seepage will be there. In that case waterproofing or any other solution to avoid water seepage shall be under Customer Scope.
15. If you are liable to deduct TDS u/s 194Q then please let us know in advance, otherwise we will have to collect TCS u/s 206CR from you @0.1% the Invoice Value and shall be recovered from you.

## NOTE:

Any change in Elevator's height, No. of spouting, No. of spout section, No. of ducting, Pit Cover, Chutes etc. as per site condition or Customer's requirement shall be charged extra as per actual.  
for OSAW AGRO INDUSTRIES PVT. LTD.

SANJEEV SAGAR  
MANAGING DIRECTOR

# OSAW AGRO INDUSTRIES PVT.LTD.

P.O. Bag 5, Agrosaw Complex, Jagadhri Road, Ambala cantt., Haryana 133001 (India)  
E-mails : agrosaw@agrosaw.com , CIN No. U29211HR2002PTC34843  
Phones : (0091) 171 2699354, 2699167, 2699547 Fax : (0091) 171 2699018  
GSTIN : 06AAACO5198C1ZJ Web : www.agrosaw.com



Our Ref :- SS/Z-1/EQ/18052

Date : Dec.11, 2021

Enq No 18045,

## YAS AGRO INDUSTRIES

NO. 22/1/C, ANGAR WAFALE ROAD,  
KHANDOBACHIWADI, TAL- MOHOL,  
SOLAPUR  
MAHARASHTRA( INDIA )  
Mobile No :9011416975  
Email : thitesac@gmail.com

Sub. :- OFFER FOR FLAT BOTTOM SILO 500 MT WITH ACCESSORIES.  
Ref :- YOUR DISCUSSION WITH MR. RAJAT PAHWA & MR. GAGANDEEP SINGH

Sr.	PARTICULARS	QTY	UNIT RATE	AMOUNT
<b><u>PART "B" SILO &amp; MATERIAL HANDLING</u></b>				
1	<b><u>AGROSAW V.B. ELEVATOR CAP. 5 TPH 21 MDH (SPS) TO FEED SILO</u></b> All sheet metal components shall be manufactured on CNC machine.  Head casing, boot casing and leg casing made of 2.0 mm, 3.0 mm and 1.6 mm of <b>275 gsm</b> GI. Sheet respectively, spouting and discharge valve made of 1.6 mm GI sheet. Complete with suitable geared motor starter and switch, service platform, ladder, one length of spouting and all standard features.  Belt shall be NN rubber belt, buckets shall be PU/Nylon/HDPE self cleaning type. Spacers shall be provided in between belt and buckets to prevent damage to seeds. Boot pulley shall be wing type to prevent lodging of seed between belt and pulley. Head pulley shall be rubberised and crowned for improved traction. Belt tensioning with bakelite slide. Sprocket shall be TLB type for easy and quick fitting. Belt speed shall not exceed 1 m/sec. (Rs. Three Lakh Eighty Eight Thousand only.)	1 No.	Rs. 3,88,000	388,000.00
<b><u>SUB-ASSEMBLIES &amp; PARTS</u></b>				
a)	<b><u>TOWER FOR VBE-21M HEIGHT</u></b>  (Rs. Four Lakh One Thousand only.)	1 No.	Rs. 4,01,000	4,01,000
2	<b><u>UNLOADING DRAG CHAIN CONVEYOR</u></b> Capacity : 5 TPH on wheat Length : 15 meters  Complete with suitable power motor and other standard features. (Rs. Four Lakh Five Thousand only.)	1 No.	Rs. 4,05,000	405,000.00

# OSAW AGRO INDUSTRIES PVT.LTD.

P.O. Bag 5, Agrosaw Complex, Jagadhri Road, Ambala cantt., Haryana 133001 (India)  
E-mails : agrosaw@agrosaw.com , CIN No. U29211HR2002PTC34843  
Phones : (0091) 171 2699354, 2699167, 2699547 Fax : (0091) 171 2699018  
GSTIN : 06AAACO5198C1ZJ Web : www.agrosaw.com



Sr.	PARTICULARS	QTY	UNIT RATE	AMOUNT
3	<u>Auto Bagging and auto pouch packing system "</u>	1 No. 1600000		1600000.00
4	<u>ADDITIONAL CONNECTION POINTS IN CONTROL PANEL</u>  (Rs. One Lakh Fifty Three Thousand Six Hundred only.)	1 No. Rs.	1,53,600	153,600.00
5	<u>INSTALLATION &amp; COMISSIONING CHARGES (WITHOUT CIVIL WORK)</u> SUPPLIER SCOPE (AGROSAW) 1.On receipt of purchase order we send Engineer at site to take measurement of building to know suitability for installation of plant. 2.After site visit, we prepare machine layout showing raw seed intake, clean seed out, position of dust collector, height of elevators etc. & send it for approval to customer. 3.On the basis of approved machine layout by purchaser, we prepare civil foundation drawing. 4.Opening of packing boxes at site. 5.Assembly & Erection of Equipment. 6.To arrange unskilled labour required for assembly & erection of plant. 7.Electrical connection to all equipment from the supplied electrical control panel. Electric control panel shall be installed at maximum distance up to 5m from the machine, distance beyond 5m shall be to the customer account, laying of cables shall be under ground in PVC pipes. 8.To provide electric cables, electric items required for electrification of complete plant. 9.Air ducting, delivery chutes & any other item required to complete the machine. 10.Commissioning & Trial of machines with the product. 11.Training to user's staff for proper maintenance, adjustment & operation of the machine. CUSTOMER/PURCHASER SCOPE 1.To unload & to transport the equipment from unloading point to installation site. 2.Proper building & space for installation & commissioning of the machines/plants & any other civil work beyond supplier scope. Installation on unfinished/incomplete flooring shall not be done by Agrosaw. 3.Electric cables from main grid to main control panel of the plant with proper earthing. 4.Facility to work at site after office hours/holidays, if required. 5.Desired height platform for fitting of dust collector outside the building. 6.To provide warehouse to store equipment which need	1 No. Rs.	3,98,500	398,500.00

# OSAW AGRO INDUSTRIES PVT.LTD.

P.O. Bag 5, Agrosaw Complex, Jagadhri Road, Ambala cantt., Haryana 133001 (India)  
E-mails : agrosaw@agrosaw.com , CIN No. U29211HR2002PTC34843  
Phones : (0091) 171 2699354, 2699167, 2699547 Fax : (0091) 171 2699018  
GSTIN : 06AAACO5198C1ZJ Web : www.agrosaw.com



Sr.	PARTICULARS	QTY	UNIT RATE	AMOUNT
	protection from bad weather conditions & thefts etc. 7.To arrange electric connection at site to run tools & equipment required for installation & commissioning of the project. 8.To arrange water for civil works & safe drinking water for work force to be engaged to install & commission the project. 9.To provide raw material (seed, grain) for trial purpose. 10.Licenses,permissions & necessary authorization for installation if required. 11.To arrange operator/Responsible Person for Operational/Maintenance works. 12. Any change in the layout after the start of installation shall be to the customer account. 13.If customer wants cable to be laid on cable trays and or in trenches then expenditure on this shall be to customer account. 14.To arrange widening of gate height & width for machine to enter in the building & after machines are shifted inside godown, then customer shall arrange the repair at his cost. 15.Noise reducing system, Fire fighting, General electric installation, Work contract tax is in the scope of the customer. 16.To arrange civil work through mason for cabling & V.B. Elevator pits, machine foundation pit etc. 17.Crane/Fork lift etc. shall be arranged by the purchaser. (Rs. Three Lakh Ninety Eight Thousand Five Hundred only.)			
	Sub Total			3,346,100.00
	DISCOUNT			836,525.00
				25,09,575.00
	TOTAL OF PART "A"			66,84,300.00
	TOTAL OF PART "A" + PART "B"			91,93,875.00
	GST @ 5%			4,59,693.00
	Transport & Insurance @5%			4,59,693.00
	<b>Grand Total -----</b>			<b>1,01,13,261.00</b>

# OSAW AGRO INDUSTRIES PVT.LTD.

P.O. Bag 5, Agrosaw Complex, Jagadhri Road, Ambala cantt., Haryana 133001 (India)  
E-mails : agrosaw@agrosaw.com , CIN No. U29211HR2002PTC34843  
Phones : (0091) 171 2699354, 2699167, 2699547 Fax : (0091) 171 2699018  
GSTIN : 06AAACO5198C1ZJ Web : www.agrosaw.com



## **TERMS & CONDITIONS**

- 1 PRICES: Our prices included all transport and insurance and GST .
- 2 PAINT: All the metallic parts of machines shall be painted in "PU" paint as standard supply in the quoted price.
- 3 Transit Insurance shall be charged extra @ 0.5% on the 110% invoice value Plus GST as applicable at the time of supply.
- 4 Unloading of equipment at site shall be arranged by the buyer at his own risk and cost.
- 5 `If there is any change in the rate of taxes and/or imposition of any new taxes at the time of supply that shall be to buyer`s account.
- 6 Validity: Our rates shall remain valid for 60 days from the date of our offer, afterward subject to confirmation.

# OSAW AGRO INDUSTRIES PVT.LTD.

P.O. Bag 5, Agrosaw Complex, Jagadhri Road, Ambala cantt., Haryana 133001 (India)  
E-mails : agrosaw@agrosaw.com , CIN No. U29211HR2002PTC34843  
Phones : (0091) 171 2699354, 2699167, 2699547 Fax : (0091) 171 2699018  
GSTIN : 06AAACO5198C1ZJ Web : www.agrosaw.com



Sr.	PARTICULARS	QTY	UNIT RATE	AMOUNT
7	Validity: Our rates shall remain valid for 60 days from the date of our offer, afterward subject to confirmation.			
8	Delivery: The equipment shall be despatched within 6 to 8 weeks from Ambala Cantt after receipt of your technically & commercially clear confirmed order. NOTE: However, because of on going Covid-19 Pandemic, we can honour the delivery schedule if the situation normalizes & we are able to undertake normal manufacturing cycle.			
9	Warranty: 12 Calendar months from the date of despatch against any manufacturing defect and/or bad workmanship.			
10	Payment: 40% payment advance alongwith your order and balance 60% payment before dispatch of machines. All the payments by Bank Draft in favour of OSAW AGRO INDUSTRIES PVT. LTD. payable at any nationalised Bank at Ambala Cantt. All Bank charges shall be to buyer's account. CC ACCOUNT No. 3887 0087 00 00 2289 IFSC CODE: PUNB0388700			
11	Service Tax @ 18% shall be charged extra on erection & commissioning charges separately.			
12	For all disputes the jurisdiction would be Ambala only.			
13	If installation of machine is to be done through Chemical Anchoring than floor must be RCC (Reinforced cement concrete) with minimum thickness of 150mm over 100mm PCC ( Plain cement concrete ) on compact soil.			
14	If the depth of water table is less than the depth of Elevator pit/foundation, chances of water seepage will be there. In that case waterproofing or any other solution to avoid water seepage shall be under Customer Scope.			
15	If you are liable to deduct TDS u/s 194Q then please let us know in advance, otherwise we will have to collect TCS u/s 206CR from you @0.1% the Invoice Value and shall be recovered from you.			

## NOTE:

Any change in Elevator's height, No. of spouting, No. of spout section, No. of ducting, Pit Cover, Chutes etc. as per site condition or Customer's requirement shall be charged extra as per actual.  
for OSAW AGRO INDUSTRIES PVT. LTD.

SANJEEV SAGAR  
MANAGING DIRECTOR